

## King Crimp Flanged Fittings

### Combination Nipple and 150# ASA Fixed (Welded) Flanges



Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturers' products with Dixon® products.

#### Feature

- There are two grooves on the crimp style King combination nipples. The second groove is the roll stamp groove, which has the part number and "call Dixon" stamped on it. This groove is a smooth concentric groove so that the stamp is legible.



stainless steel

Size	Steel Part #	316 Stainless Steel Part #
1-1/2"	FST20CS	RFST20CS
2"	FST25CS	RFST25CS
3"	FST35CS	RFST35CS
4"	FST40CS	RFST40CS
6"	FST60CS	RFST60CS

NOTE: For flange dimensions, diagrams, and additional information, please reference [dixonvalve.com](http://dixonvalve.com). For additional information on pipe dimensions, please reference [dixonvalve.com](http://dixonvalve.com).

### Combination Nipple and TTMA Flanges

#### Feature

- To be used with King Crimp sleeves and/or ferrules



carbon steel



aluminum

Size	Flange Thickness	Carbon Steel Part #	Aluminum Part #
2"	3/8"	---	ATTFST25CS
3"	1/4"	TTFST35CS	ATTFST35CS
	3/8"	---	---
4"	5/16"	TTFST40CS	ATTFST40CS
	3/8"	TTFST40CS-THK	---

NOTE: For flange dimensions, diagrams and additional information please reference [dixonvalve.com](http://dixonvalve.com). For additional information and drawings on pipe dimensions please reference [dixonvalve.com](http://dixonvalve.com).

### Nipples for Floating Flanges

#### Feature

- To be used with King Crimp sleeves and/or ferrules



carbon steel

Size	Plated Carbon Steel Part #	316 Stainless Steel Part #
2"	N25CS	RN25CS
3"	N35CS	RN35CS
4"	N40CS	RN40CS
6"	N60CS	RN60CS

NOTE: To be used with lap joint, LJ/LJR floating flanges on page 970.