

Tuff-Lite®

Hose Shank x Female NPT Insert

Features

- Nylon fittings should not be used with acid-based fertilizers, bromine, chlorine, fluorine, hydrochloric acid, iodine, nitric acid, phosphoric acid, sulfuric acid, or xylene
- Nylon should not be used with compressed gas



Hose Size	Female NPT	Nylon Part #	Pkg Qty
1/4"	1/4"	TFS22	50
1/4"	1/2"	TFS42	25
1/2"	1/2"	TFS44	25
3/4"	3/4"	TFS66	25

Hose Shank x Female NPSM

Specification

- Ball seat type



Hose Size	Female NPSM	Nylon Part #	Pkg Qty
1/4"	1/4"	TF22	1
3/8"	3/8"	TF33	1

Short Shank x Female NPSM Couplings

Features

- Sold in package quantities only
- Shipped with a red vinyl washer (TVW7), replacement washers on pages 423, 1024



Hose Shank	Female NPSM	Nylon Part #	Pkg Qty
1/4"	3/4"	TCF62	100
3/8"		TCF63	100
1/2"		TCF64	100
5/8"		TCF65	100
3/4"		TCF66	100

Tuff-Lite – Reducing Bushings



Male NPT	Female NPT	Nylon Part #	Pkg Qty
3/8"	1/4"	THB32	25
1/2"	1/4"	THB42	25
1/2"	3/8"	THB43	25
3/4"	1/2"	THB64	25
1"	3/4"	THB86	25

NOTE: For additional information on pipe dimensions please reference dixonvalve.com.