

Hand Hydrotest Pump

Application

- Designed for use in testing pipe lines, pressure tanks, and pressure vessels

Feature

- Uses check valves, which are more efficient and longer lasting than poppet systems

Material

- Stainless steel piston

Specifications

- Cylinder displacement: 1.37 cu. in.
- **0 -1000 PSI** pressure gauge, 10' high pressure hose and quick disconnect coupler included
- Piston: 7/8" with 2" stroke
- Working pressure: **1000 PSI** at 70°F (21°C)



NPT Inlet	NPT Outlet	Aluminum Part #
1/2"	1/2"	HHTP

Hydrostatic Test Pumps

Electric Test Pump

Features

- 110 volt Portable Hydrostatic Electric Pump - Model (ETP)
- Quick connect garden hose coupler for water supply line available

Specifications

- **3000 PSI** maximum test pressure
- **1.3 GPM** fill rate (at **60 PSI** inlet water pressure)
- 1/2" x 25' intermediate hose with brass straight-thru quick coupler x NPSM swivel connection
- 1/2" brass straight-thru plug on pressure outlet
- **0 – 3000 PSI** back mount liquid filled pressure gauge



Part #
ETP

Pneumatic Test Pump

Features

- Stainless interior
- Air gauge for quick, easy adjustment of maximum test pressure
- High pressure test gauge
- Filter/regulator for clean, dry air to ensure long life of unit
- On - off valve for air input
- 20' of hose included
- Easy to use: portable hand cart mount or stationary wall mount available
- Use of coalescing filter and water filter recommended for prolonged pump life

Specifications

- **5.5 GPM** fill rate
- Test pressure: **0 to 1500 PSI**



Hand Cart Mount Part #	Wall Mount Part #
PTP	PTP-WM
PTP-N ¹	PTP-N-WM ¹

¹ Includes Series 1 filter/regulator

NOTE: for accessories go to dixonvalve.com.

T