

Twist Nozzle



Specification

- Maximum operating pressure: **150 PSI** (water only)

Thread Size	Length	Required Case Qty	Extruded Brass Part #
3/4" GHT	4"	6	GHD-500AN4

Insulated Water Nozzle

Features

- Clip locks to any spray pattern
- Industrial strength nylon handle
- Rubber handle guard
- GHT thread-on head
- Heavy-duty brass valve and adjusting nut

Specification

- For use with hot water up to **140°F (60°C)**



Thread Size	Required Case Qty	Chrome-Plated Zinc Part #
3/4" GHT	4	GHD-SN75

Washers

Filter Washers



Description	Kit Contains Part #	Required Case Qty	FDA black PVC duro, 70a Part #
304 stainless steel mesh, FDA black 70a duro PVC	5911212F (4)	6	GHD-5911212F

Black SBR Washers



I.D.	O.D.	Duro	Kit Contains Part #	Required Case Qty	Black SBR Part #
0.60"	1.02"	80	5911212W (4)	100	GHD-5911212W

Female GHT Adapter



Female x Female	Required Case Qty	Brass Part #
3/4" x 3/4"	6	GHD-5061212C

Hydrant Adapters - Pin Lug



Female NH	Male GHT	Required Case Qty	Cast Brass Part #
1-1/2"	3/4"	4	GHD-HA1576
2-1/2"	3/4"	4	GHD-HA2576