

## In-Line Lubricators

### Application

- Protects portable or stationary air tools by efficiently oiling the tool mechanisms; each time an air tool is operated a fine mist of oil is injected into it along with the air from the compressor

### Features

- Installation is recommended within 25' of the tool to be lubricated; refer to the arrow for proper air flow direction
- Transparent sight disc allows visual inspection of oil level
- Oil flow regulated by screwdriver screw adjustment, minimum flow rate is 30 SCFM
- Not recommended for constant flow applications
- For reciprocating tools only
- Type of oil to use: any petroleum-based, non-detergent light weight oil (SAE 10/150SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil  
Do not use any synthetic oil or oils containing additives or solvents
- See below for air tool lubricant



| NPT Size | Oil Capacity   | Maximum Working Pressure at Ambient Temperature (70°F) | Air Flow at 70 PSI | Required Case Qty | Aluminum Part # |
|----------|----------------|--|--------------------|-------------------|-----------------|
| 1/2"     | 1.4 fluid ozs. | <b>500 PSI</b>   | 30 SCFM            | 3                 | PL300           |

NOTE: Products placed in blue plastic bin with label.

## Air Tool Lubricant

### Application

- High-grade lubricant prolongs the service life of air tools, cylinders, and accessories

### Features

- #10 weight lubricant
- Prohibits rust and removes moisture as it lubricates
- Non-corrosive, non-reactive, and does not decompose
- Easy pour spout helps prevent costly spills

| Size     | Required Case Qty | Part #  |
|----------|-------------------|---------|
| 1 pint   | 4                 | DATL016 |
| 1 gallon | 2                 | DATL128 |



## Anti-Freeze Lubricant

### Application

- Winter grade air tool lubricant prevents air line, air tool, and in-line lubricator freeze-up

### Feature

- Can be poured directly into tool or used with air line lubricators

### Specification

- Minimum temperature **-45°F (-43°C)**

| Size     | Required Case Qty | Part #   |
|----------|-------------------|----------|
| 1 pint   | 4                 | DATL016W |
| 1 gallon | 2                 | DATL128W |

