

Safety Vented Ball Valves

Application

- For air service only

Specification


- Pressure rating: **0-125 PSI**

Features

- Blow-out proof stem design
- Adjustable packing gland

Approval

- Vent downstream air in accordance with OSHA regulation 1910.147 for pneumatic systems



Materials

- Bronze valve
- Chromium plated ball
- RTFE seats and stuffing box ring

Female NPT	Port	Required Case Qty	Bronze Part #
3/4"	standard	3	BBV75LV

NOTE: Products placed in blue plastic bin with label.

Whip Hose



Description	Required Case Qty	Part #
Whip hose 1/2" x 6', Air King x 7/8" threaded bent stem	1	WH50X6AKBS87



Description	Required Case Qty	Part #
Whip hose 1/2" x 6', Air King x 1/2" threaded bent stem	1	WH50X6AKBS50



Description	Required Case Qty	Part #
Whip hose 3/4" x 6', Air King x 3500 nipple	1	WH75X6AK35

Sign Holder



Description	Required Case Qty	Part #
End cap sign holder	2	SIGNHOLDER

End Cap Sign



Description	Required Case Qty	Part #
Outside air end cap sign	1	OA-SIGN

Blue Bins with Label



Description	Required Case Qty	Contents	Part #
Blue bins with label	1	S-12416 (2) S-13536 (13) S-12414 (5)	OA-BLU-BINS

U