

ADS Outrage Gauges

Applications

- Set level fill point for manual/visual fill control
- Measure outage requirements on mobile tanks

Feature

- Open dome bracket

Material

- 316 stainless steel

Length	316 Stainless Steel Standard Outrage Gauge Part #	316 Stainless Steel Outrage Gauge with J Bar Part #
3'	A800OG3	A800OGJ3
4'	A800OG4	A800OGJ4
5'	A800OG5	A800OGJ5



outrage gauge with J bar

outrage gauge

C

ADS Gauge Rods

Application

- Used to gauge liquid levels in any mobile tank

Size

- 1/2" x .065 weight

Features

- Laser engraved scale with 1/4" graduations
- Rods come in two sections that screw together at the midpoint
- Foot marks inscribed on rod at 1' intervals below the inch mark
- Heavy-duty plastic handle

Material

- 316 stainless steel

Description	316 Stainless Steel Part #	316 Stainless Steel Part # w/sliding innage bar
gauge rod, 8' length, two piece	ADS8GR	---
gauge rod, 12' length, two piece	ADS12GR	ADS12GR-IB



laser engraving close up



ADS Spillguard® Armored Cables

Features

- 3 pin connector
- 316 stainless steel armored cable or yellow rubber cable
- Custom lengths available; call 513.874.8499 or 877.582.3569 for more information

Armored Cables

Length	3 Pin
15'	A200CA3P15
20'	A200CA3P20
25'	A200CA3P25
50'	A200CA3P50



Rubber Cable

Length	3 Pin
25'	A200CB3P25



NOTE: For use with (-M) mini connectors only