

Universal Couplings..... 190-199

Air King®190-191
 Global Air King.....192-193
 Global Air King ferrules 193
 Air King with ferrule..... 194
 Air King with gauge port 194
 Air King universal swivels 195
 Air King clamps 195
 Air King accessories 196
 Sand Blast..... 197
 Sure-Lock®198-199

Quick Disconnects..... 200-235

Dix-Lock® N-Series200-203
 Dual-Lock P-Series 204-206
 DF-series207-211
 J-series212-213
 M-series214-215
 CJ-series 216
 SHD-series217-218
 L-series 218
 U-series219
 NK-series 220
 BR-series..... 221
 A-series222-223
 Profile Chart..... 224
 Ball swivel plug..... 224
 Air Chief industrial.....225-228
 Air Chief plugs225-226
 Air Chief semi-automatic 227
 Air Chief automatic 228
 Parker® E-z-mate 229
 Legris® automatic safety couplers..... 230
 Air Chief automotive231-232
 Air Chief ARO interchange233-234
 Air Chief Lincoln interchange 235

Steel 3500 nipples..... 236

Bent Stem Swivels..... 237

DOT Air Brake..... 238-249

DOT push-in fittings238-239
 Legris DOT push-in fittings240-243
 Air brake.....244-249

Push-in..... 250-268

Brass250-253
 Stainless steel Legris.....254-255
 Nickel-plated brass Legris256-257
 Nylon/Nickel-plated brass Legris258-260, 262
 Nylon Legris..... 261
 Manifold, Legris..... 262
 Fittings kit, Legris..... 262
 Valves263-265
 Ball 263
 Quick exhaust..... 263
 Flow control.....263-264
 Check 265
 Metric.....266-268



⚠ WARNING

The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose. To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat-treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.