

EZ-P-Series Low Pressure Spring Driven Hose Reel with Hose

Features

- Compact space-saving size and heavy-duty construction make them highly versatile and virtually indestructible
- Time-tested proven components, superior design, and craftsmanship
- Multi-position lock ratchet mechanism secures hose at desired length
- Professional-grade heavy-duty steel construction
- Blue powder coat
- Rolled edges and ribbed discs provide strength and safety
- Reduce retraction speed by up to 80%
- Control hose or cord whip hazard
- Requires no external power source
- Enhances operator and workplace safety
- Keep your workplace organized, utilize space, and maximize efficiency
- Improve hose, cord, and cable management extending longevity of hose, cord, and cable

Materials

- Non-corrosive stainless steel spring, pawl, and zinc-plated ratchet
- 1" solid steel axle and lubricated precision bearings for smooth rotation

Specification

- Maximum temperature **150°F (66°C)**



F

With Hose

Hose I.D.	Hose Length	Service	Working Pressure PSI at 70°F	Steel Part #
3/8"	50'	air/water	300	EZP3850
1/2"	35'	air/water	300	EZP5050

100-Series High-Pressure Hand Crank Hose Reel without Hose

Features

- Blue powder coat
- Lightweight, compact, versatile
- Save time and effort while increasing the safety of your work environment
- Sturdy "U" shaped frame

Specification

- Maximum temperature **150°F (66°C)**

Without Hose

Hose Capacity	Service	Working Pressure PSI at 70°F	Steel Part #
50' of 3/8"	water	4000	C3850N
100' of 3/8"	water	4000	C38100N
250' of 3/8"	water	4000	C38250N



Reelcraft® 20,000 High Pressure Hand Crank Spray Reel without Hose

Features

- Powder coated aluminum
- Carbon steel swivel
- 18" spool width

Specification

- Maximum temperature **210°F (99°C)**

New

Hose I.D.	Hose Capacity	Service	Working Pressure PSI at 70°F	Part #
3/8"	500'	water	4500	C23018H
1/2"	300'			
5/8"	250'			
3/4"	200'			



NOTE: 12" and 22" spool widths available upon request