

Grease Whip Hose Assemblies

Application

- For use with hand grease guns only

Specifications

- 1/8" – 27 male NPT, solid base (0010260C)
- Working pressure: **3000 PSI**

Features

- One-piece crimp couplings
- Add "S" to order carbon steel strain relief spring option

Approval

- US-manufactured 3/16" I.D. hose - exceeds SAE 100R1-AT



Assembly Length	Brass		Strain Relief Option
	Previous Part #	Part #	
8"	GWH-0800	GWH0800	GWH0800S
12"	GWH-1200	GWH1200	GWH1200S
	---	GWH1200R ¹	---
18"	GWH-1800	GWH1800	GWH1800S
	---	GWH1800R ¹	---
24"	GWH-2400	GWH2400	GWH2400S
36"	GWH-3600	GWH3600	GWH3600S
48"	GWH-4800	GWH4800	GWH4800S
60"	GWH-6000	GWH6000	---


¹ Retail packaging

Grease Whip Hose Fittings

Features

- 0010055C, 0010260C, and 0010860C are designed to be crimped to 3/16" I.D. hose
- GWHC and GWHC-FF mate with Zerk fittings on the coupler side

Grease Hose Couplers



Description	Zinc Plated Steel		Opt Qty
	Previous Part #	Part	
1/8" – 27 female NPT thread, grease hose coupler with ball check – valved shutoff	GWH-C	GWHC	25
1/8" – 27 female NPT thread, full flow grease hose coupler	---	GWHC-FF	25


NOTE: Add 'R' suffix to part number for retail pack option.

Male NPT Thread – Chamfered Base



Description	Brass		Opt Qty
	Previous Part #	Part #	
1/8" – 27 male NPT thread, drilled and chamfered base	001-0055	0010055C	100

Male NPT Thread – Solid Base



Description	Brass		Opt Qty
	Previous Part #	Part #	
1/8" – 27 male NPT thread, solid base	001-0260	0010260C	100

Female NPT Thread



Description	Brass		Opt Qty
	Previous Part #	Part #	
1/8" – 27 female NPT thread	001-0860	0010860C	100