

H-BOP Series Hydraulic Couplings

Application

- Designed specifically for blowout preventer systems on drilling rigs

Features

- Steel coupler sleeves are hardened to resist deformation and maximize service life
- Individually marked with the BOP series designation
- Interchangeable with ISO7241 Series B, Eaton®/Hansen® HKFR-Series, DNP HNV-BOP Series

Specification


- Pressure rating **5000 PSI** at **70°F (21°C)**

Approval

- Fire tested and Lloyd's certified to **1300°F (700°C)** in accordance with API 16D; certificate available upon request

Blowout Preventer Safety Female Couplers

Body Size	Female Threads	Steel Part #	316 Stainless Steel Part #
3/8"	3/8" – 18 NPTF	3HF3-BOP	3HF3-SS-BOP
1/2"	1/2" – 14 NPTF	4HF4-BOP	4HF4-SS-BOP
3/4"	3/4" – 14 NPTF	6HF6-BOP	6HF6-SS-BOP
1"	1" – 11-1/2 NPTF	8HF8-BOP	8HF8-SS-BOP



Blowout Preventer Safety Female Plugs

Body Size	Female Threads	Steel Part #	316 Stainless Steel Part #
3/8"	3/8" – 18 NPTF	H3F3-BOP	H3F3-SS-BOP
1/2"	1/2" – 14 NPTF	H4F4-BOP	H4F4-SS-BOP
3/4"	3/4" – 14 NPTF	H6F6-BOP	H6F6-SS-BOP
1"	1" – 11-1/2 NPTF	H8F8-BOP	H8F8-SS-BOP

