

## K-Series Hydraulic Couplings

### Features

- Poppet style shut-off valves in both coupler and plug
- Interchangeable with Aeroquip®/Eaton® FD56 (5600), ISO-A 7241 interchange, Stucchi® BIR, Parker® 6600-Series, Faster® ANV, and Safeway® S56-Series. See Hydraulic Profile Chart on page 504
- Contact Dixon® for additional seal material options, pressure ratings and other technical information

### Specification

- Nitrile rubber seal standard, providing a temperature range of -40°F to 250°F (-40°C to 121°C)

### ISO-A Interchange Female Threaded Couplers

Body Size	Threads	Steel Part #	316 Stainless Steel Part #
1/4"	1/8" – 27 NPTF	2KF1	---
	1/4" – 18 NPTF	2KF2	2KF2-SS
	1/4" – 19 BSPP	2KBF2	2KBF2-SS
	7/16" – 20 ORB	2KOF2	---
3/8"	3/8" – 18 NPTF	3KF3	3KF3-SS
	3/8" – 19 BSPP	3KBF3	3KBF3-SS
	9/16" – 18 ORB	3KOF3	---
1/2"	1/2" – 14 NPTF	4KF4	4KF4-SS
	1/2" – 14 BSPP	4KBF4	4KBF4-SS
	3/4" – 16 ORB	4KOF4	---
	7/8" – 14 ORB	4KOF5	---
	3/4" – 14 NPTF	4KF6	---
3/4"	3/4" – 14 NPTF	6KF6	6KF6-SS
	3/4" – 14 BSPP	6KBF6	6KBF6-SS
	1-1/16" – 12 ORB	6KOF6	---
1"	1" – 11-1/2 NPTF	8KF8	8KF8-SS
	1" – 11 BSPP	8KBF8	8KBF8-SS
	1-5/16" – 12 ORB	8KOF8	---
1-1/4"	1-1/4" – 11-1/2 NPT	10KF10	---
	1-1/4" – 11 BSPP	10KBF10	---
1-1/2"	1-1/2" – 11-1/2 NPT	12KF12	---
	1-1/2" – 11 BSPP	12KBF12	---
2"	2" – 11-1/2 NPT	16KF16	---
	2" – 11 BSPP	16KBF16	---



4KF4 - steel



6KF6 - steel



10KF10 - steel

