

**HT-Series Correct Connect®**

**Features**

- Minimizes fluid loss resulting in a cleaner, safe work environment
- Automatic, push-to-connect couplings provide high flow with minimal pressure drop assuring maximum hydraulic system performance
- To reduce the possibility of accidental disconnect, the sleeve lock safety feature requires turning the collar to unlock the coupling
- Contact Dixon® for additional seal material options, pressure ratings, and other technical information

**Approvals**

- Conforms to ISO16028 interchange standard; interchangeable with Eaton®/Hansen® FF, Faster® FFH/2FFN/2FFI, Stucchi® A/FIRG, and Holmbury® HQ/A/FIMC

**ISO16028 Flush Face Female Threaded Couplers**

Body Size	Threads	Steel Part #	316 Stainless Steel Part #
1/4"	1/4" – 18 NPTF	2HTF2	---
	1/4" – 19 BSPP	2HTBF2	---
	9/16" – 18 ORB	2HTOF3	---
3/8"	3/8" – 18 NPTF	3HTF3	3HTF3-SS
	3/8" – 19 BSPP	3HTBF3	3HTBF3-SS
	9/16" – 18 ORB	3HTOF3	---
	1/2" – 14 NPTF	3HTF4	3HTF4-SS
	1/2" – 14 BSPP	3HTBF4	3HTBF4-SS
	3/4" – 16 ORB	3HTOF4	---
	1/2" – 14 NPTF	4HTF4	4HTF4-SS
1/2"	1/2" – 14 BSPP	4HTBF4	4HTBF4-SS
	3/4" – 16 ORB	4HTOF4	---
	7/8" – 14 ORB	4HTOF5	---
	3/4" – 14 NPTF	4HTF6	4HTF6-SS
	3/4" – 14 BSPP	4HTBF6	4HTBF6-SS
	1-1/16" – 12 ORB	4HTOF6	---
	7/8" – 14 ORB	5HTOF5	---
5/8"	3/4" – 14 NPTF	5HTF6	5HTF6-SS
	3/4" – 14 BSPP	5HTBF6	5HTBF6-SS
	1-1/16" – 12 ORB	5HTOF6	---
	7/8" – 14 ORB	6HTOF5	---
3/4"	3/4" – 14 NPTF	6HTF6	6HTF6-SS
	3/4" – 14 BSPP	6HTBF6	6HTBF6-SS
	1-1/16" – 12 ORB	6HTOF6	---
	1" – 11-1/2 NPTF	6HTF8	6HTF8-SS
	1" – 11 BSPP	6HTBF8	6HTBF8-SS
	1-5/16" – 12 ORB	6HTOF8	---
	1" – 11-1/2 NPTF	8HTF8	8HTF8-SS
1"	1" – 11 BSPP	8HTBF8	8HTBF8-SS
	1-5/16" – 12 ORB	8HTOF8	---
	1-1/4" – 11-1/2 NPTF	8HTF10	8HTF10-SS
	1-1/4" – 11 BSPP	8HTBF10	8HTBF10-SS
	1-5/8" – 12 ORB	8HTOF10	---
	1-1/2" – 11-1/2 NPTF	12HTF12	---
1-1/2"	1-1/2" – 11 BSPP	12HTBF12	---
	1-7/8" – 12 ORB	12HTOF12	---
	2" – 11-1/2 NPTF	16HTF16	---
2"	2" – 11 BSPP	16HTBF16	---
	2-1/2" – 12 ORB	16HTOF16	---



steel



316 stainless



3HTM3



3HTOM4

**ISO16028 Flush Face Male Threaded Couplers**

Body Size	Threads	Steel Part #
3/8"	3/8" – 18 NPTF	3HTM3
	1/2" – 14 NPTF	3HTM4
	9/16" – 18 ORB	3HTOM3
	3/4" – 16 ORB	3HTOM4
1/2"	1/2" – 14 NPTF	4HTM4