

HTE-Series Correct Connect® Connect Under Pressure Flush Face Female Threaded Plug

Features

- Head pressure or valve bleed-by has minimal effect on connection force
- Less susceptible to system contamination
- Design is scalable, performing similarly in all sizes
- Smooth connection action
- Connectable with trapped pressure on HTE half only
- For use with HTZ- or HT-Series couplers


Specifications

- No maximum connection-pressure restrictions, up to **5,000 PSI**
- Pressure rating: **5,000 PSI at 70°F (21°C)**

Approval

- Conforms to ISO16028
- Interchanges with Parker® FEC-Series, Stucchi® APM-Series, and Faster® 3FFH-Series

Body Size	Threads	Steel Part #
3/8"	3/8" – 18 NPTF	HTE3F3
	1/2" – 14 NPTF	HTE3F4
	1/2" – 14 BSPP	HTE3BF4
	3/4" – 16 ORB	HTE3OF4
1/2"	1/2" – 14 NPTF	HTE4F4
	1/2" – 14 BSPP	HTE4BF4
	3/4" – 16 ORB	HTE4OF4
	7/8" – 14 ORB	HTE4OF5
	3/4" – 14 NPTF	HTE4F6
	3/4" – 14 BSPP	HTE4BF6
	1-1/16" – 12 ORB	HTE4OF6
5/8"	7/8" – 14 ORB	HTE5OF5
	3/4" – 14 NPTF	HTE5F6
	3/4" – 14 BSPP	HTE5BF6
	1-1/16" – 12 ORB	HTE5OF6
3/4"	3/4" – 14 NPTF	HTE6F6
	3/4" – 14 BSPP	HTE6BF6
	1-1/16" – 12 ORB	HTE6OF6
	1" – 11-1/2 NPTF	HTE6F8
	1" – 11 BSPP	HTE6BF8
	1-5/16" – 12 ORB	HTE6OF8
	1" – 11-1/2 NPTF	HTE8F8
1"	1" – 11 BSPP	HTE8BF8
	1-5/16" – 12 ORB	HTE8OF8
	1-1/4" – 11-1/2 NPTF	HTE8F10
	1-1/4" – 11 BSPP	HTE8BF10
	1-5/8" – 12 ORB	HTE8OF10



K