

VEP-Series Hydraulic Couplings

Features

- No-spill, flush face valve minimizes air inclusion during connection and spillage during disconnection
- Thread-to-connect design and dual valve system in the plug allow for connecting under pressure
- Design eliminates premature wear or brinelling commonly found with locking ball designs when subjected to high impulse pressures
- Zinc nickel plating provides superior corrosion resistance
- Interchangeable with Stucchi® VEP, DNP PST 4/FSI, Holmbury® HFT, Parker® FET-Series, and Voswinkel® FT-Series
- Contact Dixon® for pressure ratings and other technical information

Female Threaded Couplers

Body Size	Threads	Steel Part #
1/4"	1/4" – 18 NPTF	2VEPF2
	1/4"- 19 BSPP	2VEPBF2
	9/16" – 18 ORB	2VEPOF3
3/8"	3/8" – 18 NPTF	3VEPF3
	3/8" – 19 BSPP	3VEPBF3
	3/4" – 16 ORB	3VEPOF4
	1/2" – 14 NPTF	3VEPF4
1/2"	1/2" – 14 BSPP	3VEPBF4
	1/2" – 14 NPTF	4VEPF4
	1/2" – 14 BSPP	4VEPBF4
	3/4" – 16 ORB	4VEPOF4
	7/8" – 14 ORB	4VEPOF5
3/4"	3/4" – 14 NPTF	4VEPF6
	3/4" – 14 BSPP	4VEPBF6
	1-1/16" – 12 ORB	4VEPOF6
	3/4" – 14 NPTF	6VEPF6
	3/4" – 14 BSPP	6VEPBF6
	1-1/16" – 12 ORB	6VEPOF6
1"	1" – 11-1/2 NPTF	8VEPF8
	1" – 11 BSPP	8VEPBF8
	1-5/16" – 12 ORB	8VEPOF8
1-1/4"	1-1/4" – 11-1/2 NPTF	10VEPF10
	1-1/4" – 11 BSPP	10VEPBF10
	1-5/8" – 12 ORB	10VEPOF10
1-1/2"	1-1/2" – 11-1/2 NPTF	12VEPF12
	1-1/2" – 11 BSPP	12VEPBF12
	1-7/8" – 12 ORB	12VEPOF12
2"	2" – 11-1/2 NPTF	16VEPF16
	2" – 11 BSPP	16VEPBF16
	2-1/2" – 12 ORB	16VEPOF16



316 Stainless Steel VEP-Series

Body Size	Threads	Style	316 Stainless Steel Part #
1"	1" – 11-1/2 NPTF	coupler	8VEPF8-SS
		plug	VEP8F8-SS