

T-Series Hydraulic Couplings

Application

- Designed for high pressure applications including hydraulic rams and pumps where low flow and pressures up to **10,000 PSI** are encountered

Features

- Interchangeable with Enerpac® C 604, Parker®/Pioneer® 3000-Series, Stucchi® IVHP, Eaton® WS5600, and DNP PVM
- Both poppet valve and ball valve styles available

Specification

- Nitrile O-ring with TPC-ET back up ring standard providing a temperature range of **-40°F to 250°F (-40°C to 121°C)**



Female NPTF Ball Coupler

Body Size	Threads	Steel Part #
1/4"	1/4" – 18 NPTF	2TF2
3/8"	3/8" – 18 NPTF	3TF3



Male NPTF Ball Couplers

Body Size	Threads	Steel Part #	Threads	316 Stainless Steel Part #
1/4"	1/4" – 18 NPTF	2TM2	---	---
3/8"	3/8" – 18 NPTF	3TM3	3/8" – 18 NPT	3TM3-SS

Male NPTF Poppet Couplers



Body Size	Threads	Steel Part #	316 Stainless Steel Part #
3/8"	3/8" – 18 NPT	3TM3-PV	3TM3-SS-PV

Female NPTF Ball Plugs



Body Size	Threads	Steel Part #	Threads	316 Stainless Steel Part #
1/4"	1/4" – 18 NPTF	T2F2	---	---
3/8"	3/8" – 18 NPTF	T3F3	3/8" – 18 NPT	T3F3-SS

Female NPTF Poppet Plugs



Body Size	Threads	Steel Part #	316 Stainless Steel Part #
3/8"	3/8" - 18 NPT	T3F3-PV	T3F3-SS-PV

K