

Hydraulic Adapters – O-ring Boss®

Port Reducers

Specification

- Pressure rating at 70°F (21°C)

| Male SAE O-ring Boss | Female O-ring Port | PSI | Zinc Plated Steel Part # |
|----------------------|--------------------|------|--------------------------|
| 9/16" – 18 | 7/16" – 20 | 5000 | 6410-6-4 |
| | 3/4" – 16 | 4500 | 6410-6-8 |
| 3/4" – 16 | 7/8" – 14 | 3500 | 6410-8-10 |
| | 9/16" – 18 | 4500 | 6410-8-6 |
| 7/8" – 14 | 1-1/16" – 12 | 3500 | 6410-10-12 |
| | 3/4" – 16 | | 6410-10-8 |
| 1-1/16" – 12 | 7/8" – 14 | 3000 | 6410-12-10 |
| | 1-5/16" – 12 | | 6410-12-16 |




Adjustable Unions

Specification

- Pressure rating at 70°F (21°C)

| Male O-ring Boss | Adjustable O-ring Boss | PSI | Zinc Plated Steel Part # |
|------------------|------------------------|------|--------------------------|
| 7/16" – 20 | 7/16" – 20 | 4500 | 6403-4 |
| 9/16" – 18 | 9/16" – 18 | 4000 | 6403-6 |
| 3/4" – 16 | 3/4" – 16 | | 6403-8 |
| 7/8" – 14 | 7/8" – 14 | 3000 | 6403-10 |
| 1-1/16" – 12 | 1-1/16" – 12 | | 6403-12 |
| 1-5/16" – 12 | 1-5/16" – 12 | 2500 | 6403-16 |




Male JIC x Male SAE

Specifications

- Reference SAE 070120
- Pressure rating at 70°F (21°C)

| Male JIC | Male SAE O-ring Boss | PSI | Zinc Plated Steel Part # |
|--------------|----------------------|------|--------------------------|
| 7/16" – 20 | 7/16" – 20 | 5000 | 1231-04-04 |
| | 9/16" – 18 | | 1231-04-06 |
| 1/2" – 20 | 3/4" – 16 | 4500 | 1231-04-08 |
| | 1/2" – 20 | | 1231-05-05 |
| 9/16" – 18 | 7/16" – 20 | 5000 | 1231-06-04 |
| | 9/16" – 18 | | 1231-06-06 |
| | 3/4" – 16 | 4500 | 1231-06-08 |
| | 7/8" – 14 | | 1231-06-10 |
| 3/4" – 16 | 9/16" – 18 | 4500 | 1231-08-06 |
| | 3/4" – 16 | | 1231-08-08 |
| | 7/8" – 14 | 3500 | 1231-08-10 |
| | 1-1/16" – 12 | | 1231-08-12 |
| 7/8" – 14 | 3/4" – 16 | 3500 | 1231-10-08 |
| | 7/8" – 14 | | 1231-10-10 |
| | 1-1/16" – 12 | | 1231-10-12 |
| 1-1/16" – 12 | 7/8" – 14 | 3000 | 1231-12-10 |
| | 1-1/16" – 12 | | 1231-12-12 |
| | 1-5/16" – 12 | | 1231-12-16 |
| 1-5/16" – 12 | 1-1/16" – 12 | 3000 | 1231-16-12 |
| | 1-5/16" – 12 | | 1231-16-16 |
| | 1-5/8" – 12 | | 1231-16-20 |
| 1-6/8" – 12 | 1-5/16" – 12 | 2500 | 1231-20-16 |
| 1-5/8" – 12 | 1-5/8" – 12 | | 1231-20-20 |



K

Male x Male NPTF

Specification

- Pressure rating at 70°F (21°C)

| Male SAE O-ring Boss | Male NPTF Pipe Adapter | PSI | Zinc Plated Steel Part # |
|----------------------|------------------------|----------|--------------------------|
| 7/16" – 20 | 1/4" – 18 | 5000 | 6401-4-4 |
| | 1/4" – 18 | 4000 | 6401-6-4 |
| 9/16" – 18 | 3/8" – 18 | | 4000 |
| | 1/2" – 14 | 6401-6-8 | |
| 3/4" – 16 | 3/8" – 18 | 3000 | 6401-8-6 |
| | 1/2" – 14 | | 6401-8-8 |
| 7/8" – 14 | 1/2" – 14 | 2500 | 6401-10-8 |
| 1-1/16" – 12 | 3/4" – 14 | | 6401-12-12 |
| 1-5/16" – 12 | 1" – 11-1/2 | 2000 | 6401-16-16 |

