

Hydraulic Adapters – O-ring Boss® (ORB)

45° Male SAE x Male JIC Elbows

Specifications

- Reference SAE 070320
- Pressure rating at 70°F (21°C)

Male SAE O-ring Boss	Male JIC	PSI	Zinc Plated Steel Part #
7/16" – 20	7/16" – 20	5000	1240-04-04
9/16" – 18	9/16" – 18		1240-06-06
3/4" – 16	3/4" – 16	4500	1240-06-08
	9/16" – 18		1240-08-06
	3/4" – 16		1240-08-08
7/8" – 14	7/8" – 14	3500	1240-08-10
	3/4" – 16		1240-10-08
	7/8" – 14		1240-10-10
1-1/16" – 12	1-1/16" – 12	3000	1240-10-12
	7/8" – 14		1240-12-10
	1-1/16" – 12		1240-12-12
1-5/16" – 12	1-5/16" – 12	2500	1240-12-16
1-5/8" – 12	1-5/16" – 12		1240-16-16
1-5/8" – 12	1-5/16" – 12	3000	1240-20-16
	1-5/8" – 12		1240-20-20



Male 37° Flare x Male Branch Tees

Specifications

- Reference SAE 070429
- Pressure rating at 70°F (21°C)

(2) Male JIC 37°	Male SAE O-ring Boss	PSI	Zinc Plated Steel Part #
7/16" – 20	7/16" – 20	5000	6803-4
9/16" – 18	9/16" – 18		6803-6
3/4" – 16	3/4" – 16	4500	6803-8
7/8" – 14	7/8" – 14		6803-10
1-1/16" – 12	1-1/16" – 12	3500	6803-12
1-5/16" – 12	1-5/16" – 12		6803-16



K

SAE Plugs

Specifications

- Reference SAE 090109A
- Pressure rating at 70°F (21°C)

Male SAE O-ring Boss	PSI	Zinc Plated Steel Part #
7/16" – 20	5000	1255-04H
9/16" – 18		1255-06H
3/4" – 16	4500	1255-08H
7/8" – 14		1255-10H
1-1/16" – 12	3500	1255-12H
1-5/16" – 12		1255-16H
1-5/8" – 12	2500	1255-20H
1-7/8" – 12		1255-24H
2-1/2" – 12	1500	1255-32H



Hollow Hex Plugs

Specifications

- Reference SAE 090109B
- Pressure rating at 70°F (21°C)
- Requires Allen wrench

Male SAE O-ring Boss	PSI	Zinc Plated Steel Part #
7/16" – 20	5000	6408HHP-4
9/16" – 18		6408HHP-6
3/4" – 16	4500	6408HHP-8
7/8" – 14		6408HHP-10
1-1/16" – 12	3500	6408HHP-12
1-5/16" – 12		6408HHP-16
1-5/8" – 12	2500	6408HHP-20
1-7/8" – 12		6408HHP-24
2-1/2" – 12	1500	6408HHP-32

