

Hydraulic Adapters – 37° JIC

Female Swivel x Male NPTF

Specification

- Pressure rating at 70°F (21°C)

Female JIC 37° Swivel	Male NPTF Pipe	PSI	Zinc Plated Steel Part #
7/16" – 20	1/8" – 27	4500	6505-4-2
	1/4" – 18		6505-4-4
1/2" – 20	1/4" – 18	4000	6505-5-4
	3/8" – 18		6505-6-4
9/16" – 18	3/8" – 18	3000	6505-6-6
	1/2" – 14		6505-8-8
3/4" – 16	1/2" – 14	2500	6505-10-8
	3/4" – 14		6505-10-12
7/8" – 14	1/2" – 14	3000	6505-12-8
	3/4" – 14		6505-12-12
1-1/16" – 12	3/4" – 14	2500	6505-16-12
	1" – 1/2		6505-16-16
1-5/16" – 12	1-1/4" – 11-1/2	2000	6505-20-20
1-5/8" – 12	1-1/2" – 11-1/2	1150	6505-24-24
1-7/8" – 12	2" – 11-1/2	1000	6505-32-32



Female Swivel x Female NPTF

Specification

- Pressure rating at 70°F (21°C)

Female JIC 37° Swivel	Female NPTF	PSI	Zinc Plated Steel Part #
7/16" – 20	1/4" – 18	4500	6506-4-4
	3/8" – 18		6506-4-6
9/16" – 18	1/4" – 18	4000	6506-6-4
	3/8" – 18		6506-6-6
3/4" – 16	1/2" – 14	3000	6506-8-8
	7/8" – 14		6506-10-8
1-1/16" – 12	3/4" – 14	2500	6506-12-12
	1" – 11-1/2		6506-16-16



K

90° Male Flare Elbows

Specifications

- Reference SAE 070201
- Pressure rating at 70°F (21°C)

Male JIC 37° Flare	Male JIC 37° Flare	PSI	Zinc Plated Steel Part #
7/16" – 20	7/16" – 20	5000	1234-04-04
9/16" – 18	9/16" – 18		1234-06-06
3/4" – 16	3/4" – 16	4500	1234-08-08
7/8" – 14	7/8" – 14		1234-10-10
1-1/16" – 12	1-1/16" – 12	3500	1234-12-12
1-5/16" – 12	1-5/16" – 12		1234-16-16
1-5/8" – 12	1-5/8" – 12	2500	1234-20-20



90° Male Flare x Female Flare Swivel Elbows

Specifications

- Reference SAE 070221
- Pressure rating at 70°F (21°C)

Male 37° JIC Flare	Female 37° JIC Swivel	PSI	Zinc Plated Steel Part #
7/16" – 20	7/16" – 20	5000	6500-4
	9/16" – 18		6500-6
9/16" – 18	7/16" – 20	4500	6500-6-4
	3/4" – 16		6500-6-8
3/4" – 16	3/4" – 16	3500	6500-8
	9/16" – 18		6500-8-6
7/8" – 14	7/8" – 14	3000	6500-8-10
	7/8" – 14		6500-10
1-1/16" – 12	1-1/16" – 12	3000	6500-12
	7/8" – 14		6500-12-10
1-5/16" – 12	1-5/16" – 12	3000	6500-16
1-5/8" – 12	1-5/8" – 12	2500	6500-20

