

Hydraulic Adapters – NPTF

Male Pipe Tees

Specifications

- Reference SAE 140437
- Pressure rating at 70°F (21°C)

Male NPTF (3)	PSI	Zinc Plated Steel Part #
1/4" – 18	5000	5600-4
3/8" – 18	4000	5600-6
1/2" – 14	3000	5600-8
3/4" – 14	2500	5600-12
1" – 11-1/2	2000	5600-16




Male x Female Pipe Tees

Specifications

- Reference SAE 140427
- Pressure rating at 70°F (21°C)

Male NPTF (2)	Female NPTF	PSI	Zinc Plated Steel Part #
1/4" – 18	1/4" – 18	5000	5601-4
3/8" – 18	3/8" – 18	4000	5601-6
1/2" – 14	1/2" – 14	3000	5601-8
3/4" – 14	3/4" – 14	2500	5601-12
1" – 11-1/2	1" – 11-1/2	2000	5601-16



Female x Male Branch Tees

Specifications

- Reference SAE 140425
- Pressure rating at 70°F (21°C)

Female NPTF (2)	Male NPTF	PSI	Zinc Plated Steel Part #
1/4" – 18	1/4" – 18	5000	5604-4
3/8" – 18	3/8" – 18	4000	5604-6
1/2" – 14	1/2" – 14	3000	5604-8
3/4" – 14	3/4" – 14	2500	5604-12
1" – 11-1/2	1" – 11-1/2	2000	5604-16




K

Female Pipe Tees

Specifications

- Reference 140438
- Pressure rating at 70°F (21°C)

Female NPTF (3)	PSI	Zinc Plated Steel Part #
1/4" – 18	5000	5605-4
3/8" – 18	4000	5605-6
1/2" – 14	3000	5605-8
3/4" – 14	2500	5605-12
1" – 11-1/2	2000	5605-16



Male x Female Run Tees

Specifications

- Reference 140424
- Pressure rating at 70°F (21°C)

Male NPTF	Female NPTF (2)	PSI	Zinc Plated Steel Part #
1/8" – 27	1/8" – 27	5000	5602-2
1/4" – 18	1/4" – 18		5602-4
3/8" – 18	3/8" – 18	4000	5602-6
1/2" – 14	1/2" – 14	3000	5602-8
3/4" – 14	3/4" – 14	2500	5602-12
1" – 11-1/2	1" – 11-1/2	2000	5602-16
1-1/4" – 11-1/2	1-1/4" – 11-1/2	1150	5602-20
1-1/2" – 11-1/2	1-1/2" – 11-1/2	1000	5602-24

