

Hydraulic Adapters – NPTF

Female Hex Caps

Specification

- Pressure rating at 70°F (21°C)



| Female NPTF | PSI | Zinc Plated Steel Part # |
|-----------------|------|--------------------------|
| 1/8" – 27 | 5000 | 5406C-2 |
| 1/4" – 18 | | 5406C-4 |
| 3/8" – 18 | 4000 | 5406C-6 |
| 1/2" – 14 | 3000 | 5406C-8 |
| 3/4" – 14 | 2500 | 5406C-12 |
| 1" – 11-1/2 | 2000 | 5406C-16 |
| 1-1/4" – 11-1/2 | 1150 | 5406C-20 |
| 1-1/2" – 11-1/2 | 1000 | 5406C-24 |

Male Hex Plugs

Specifications

- Reference SAE 130109C
- Pressure rating at 70°F (21°C)



| Male NPTF | PSI | Zinc Plated Steel Part # |
|-----------------|------|--------------------------|
| 1/8" – 27 | 5000 | 1251-02H |
| 1/4" – 18 | | 1251-04H |
| 3/8" – 18 | 4000 | 1251-06H |
| 1/2" – 14 | 3000 | 1251-08H |
| 3/4" – 14 | 2500 | 1251-12H |
| 1" – 11-1/2 | 2000 | 1251-16H |
| 1-1/4" – 11-1/2 | 1150 | 1251-20H |

Male JIC 37° Flare x Male Metric Parallel Thread

Specification

- Pressure rating at 70°F (21°C)




| Male JIC 37° Flare | Male Metric Parallel | Zinc Plated Steel Part # |
|--------------------|----------------------|--------------------------|
| 7/16" – 20 | M10X1.0 | M7400-4-10 |
| | M12X1.5 | M7400-4-12 |
| 9/16" – 18 | M14X1.5 | M7400-6-14 |
| | M16X1.5 | M7400-6-16 |
| 3/4" – 16 | M16X1.5 | M7400-8-16 |
| | M18X1.5 | M7400-8-18 |
| 1-1/16" – 12 | M22X1.5 | M7400-12-22 |
| | M27X2.0 | M7400-12-27 |
| 1-5/16" – 12 | M33X2.0 | M7400-16-33 |

Female Pipe x Male Metric Parallel Thread

Specification

- Pressure rating at 70°F (21°C)



| Female NPTF | Male Metric Parallel | Zinc Plated Steel Part # |
|-------------|----------------------|--------------------------|
| 1/4" – 18 | M12X1.5 | M7455-4-12 |
| | M14X1.5 | M7455-4-14 |
| 3/8" – 18 | M16X1.5 | M7455-6-16 |
| | M18X1.5 | M7455-6-18 |
| 1/2" – 14 | M16X1.5 | M7455-8-16 |
| | M18X1.5 | M7455-8-18 |
| 3/4" – 14 | M22X1.5 | M7455-8-22 |
| | M27X2.0 | M7455-12-27 |
| 1" – 11-1/2 | M33X2.0 | M7455-16-33 |

K