


External Swage Stems – Female End



two piece design
1"



one piece design
1-1/4" - 2"

| Size | Hose O.D. | | Plated Carbon Steel Part # |
|------|-----------|----------|----------------------------|
| | From | To | |
| 1" | 1-30/64" | 1-34/64" | TF16WF1-80 |
| | 1-34/64" | 1-38/64" | TF16WF2-80 |
| 2" | 2-36/64" | 2-40/64" | TF32WF1-80 ¹ |
| | 2-41/64" | 2-48/64" | TF32WF2-80 ¹ |

¹ Special pusher required for 1-1/4" and 2" sizes: 1-1/4" 25PUSH125-MOD, 2" 25PUSH200MOD

External Swage Uni-Range Male Couplings

Applications

- Recommended for use on most 1 or 2-wire braid reinforced hoses, fiber reinforced (braided or spiral) with or without helical wire such as chemical, high pressure air and water hoses, and LP gas hoses

Features

- Designed for smaller hose systems, hose I.D.s of 1/4" to 1"
- Shipped complete with factory assembled stem and ferrule combination
- Can be swaged or crimped
- Stainless steel stems are investment cast
- Other hose O.D.s available; consult Dixon®



| Size | Hose O.D. | | Plated Carbon Steel Part # | Stainless / Carbon Steel Part # | Stainless Steel Part # |
|------|-----------|----------|----------------------------|---------------------------------|------------------------|
| | From | To | | | |
| 1/4" | 34/64" | 38/64" | 4P1 | --- | --- |
| | 38/64" | 42/64" | 4P2 | --- | --- |
| | 42/64" | 46/64" | 4P3 | --- | --- |
| 3/8" | 46/64" | 50/64" | 6P1 | --- | --- |
| | 50/64" | 54/64" | 6P2 | --- | --- |
| | 54/64" | 58/64" | 6P3 | --- | --- |
| 1/2" | 54/64" | 58/64" | 8P1 | --- | --- |
| | 58/64" | 62/64" | 8P2 | --- | R8P2SS |
| | 62/64" | 1-2/64" | 8P3 | --- | --- |
| 3/4" | 1-6/64" | 1-12/64" | --- | --- | R12P1250 |
| | 1-10/64" | 1-14/64" | 12P1 | R12P1 | --- |
| | 1-13/64" | 1-22/64" | --- | --- | R12P1370 |
| | 1-14/64" | 1-18/64" | 12P2 | R12P2 | --- |
| | 1-18/64" | 1-22/64" | 12P3 | R12P3 | --- |
| 1" | 1-30/64" | 1-34/64" | 16P1 | R16P1 | --- |
| | 1-30/64" | 1-38/64" | --- | --- | R16P1620 |
| | 1-34/64" | 1-38/64" | 16P2 | R16P2 | --- |
| | 1-38/64" | 1-42/64" | 16P3 | R16P3 | --- |
| | 1-38/64" | 1-46/64" | --- | --- | R16P1770 |
| | 1-42/64" | 1-46/64" | 16P4 | R16P4 | --- |