

Tube Hex Hangers

Hex Hanger with Rubber Grommets and 3/8" NPT – B24RGC

Features

- Coupler is 3/8" NPT thread
- Optional: 1/2"-13 all thread or 3/8"-16 all thread

Specification

- Rubber grommets temperature range: -40°F to 257°F (-40°C to 125°C)


3/8" NPT

Tube O.D.	A (in)	B (in)	C (in)	Grommet Qty	304 Stainless Steel Part #
1/2" – 3/4"	3.43	1.45	0.75	3	B24RGC-G75
1"					B24RGC-G100
1-1/2"	4.00	2.13			B24RGC-G150
2"	4.50	2.50			B24RGC-G200
2-1/2"	4.75	1.13			B24RGC-G250
3"	5.50	3.75			B24RGC-G300
4"	6.75	4.75		4	B24RGC-G400
6"	9.25	6.63		5	B24RGC-G600
8"	11.50	8.63			B24RGC-G800



3/8"-16

Tube O.D.	A (in)	B (in)	C (in)	Grommet Qty	304 Stainless Steel Part #
1/2" – 3/4"	3.43	1.45	0.75	3	B24RGC16-G75
1"					B24RGC16-G100
1-1/2"	4.00	2.13			B24RGC16-G150
2"	4.50	2.50			B24RGC16-G200
2-1/2"	4.75	1.13			B24RGC16-G250
3"	5.50	3.75			B24RGC16-G300
4"	6.75	4.75		4	B24RGC16-G400
6"	9.25	6.63		5	B24RGC16-G600
8"	11.50	8.63			B24RGC16-G800



M

1/2"-13

Tube O.D.	A (in)	B (in)	C (in)	Grommet Qty	304 Stainless Steel Part #
1/2" – 3/4"	3.43	1.45	0.75	3	B24RGC13-G75
1"					B24RGC13-G100
1-1/2"	4.00	2.13			B24RGC13-G150
2"	4.50	2.50			B24RGC13-G200
2-1/2"	4.75	1.13			B24RGC13-G250
3"	5.50	3.75			B24RGC13-G300
4"	6.75	4.75		4	B24RGC13-G400
6"	9.25	6.63		5	B24RGC13-G600
8"	11.50	8.63			B24RGC13-G800