



500# Single Jacket All Polyester Fire Hose

Applications

- Wildland and forestry firefighting
- Industrial and commercial standpipe systems
- Utility and washdown applications

Features

- Other threads and configurations are available; contact Dixon®
- Made in the USA

Approvals

- Underwriters Listed
- Meets current NFPA 1960 standard

Materials

- Outer construction: single jacket, all polyester
- Updated tube construction: thermoplastic polyurethane liner, EPDM available on special request, coupled synthetic lining

Specifications

- Burst pressure: **750 PSI** at ambient temperature **70°F (21°C)**
- Service test pressure: **500 PSI** at ambient temperature **70°F (21°C)**
- Working pressure: **250 PSI** at ambient temperature **70°F (21°C)**

Uncoupled



Size	Bowl (Hose O.D.)	Length	Part #
1"	1-3/16"	50'	A510-50UC
		100'	A510-100UC
1-1/2"	1-3/4"	50'	A515-50UC
		100'	A515-100UC
2"	2-1/4"	50'	A520-50UC
		100'	A520-100UC
2-1/2"	2-3/4"	50'	A525-50UC
		100'	A525-100UC
3"	3-1/4"	50'	A530-50UC
		100'	A530-100UC

Coupled with Female and Male Expansion Ring Couplings



Size	Length	Rocker Lug Aluminum NST (NH) Part #	Rocker Lug Brass NST (NH) Part #	Rocker Lug Aluminum NPSH Part #
1"	50'	A510-50RAF	---	A510-50RAS
	100'	A510100RAF	---	A510100RAS
1-1/2"	25'	A515-25RAF	A515-25RBF	A515-25RAS
	50'	A515-50RAF	A515-50RBF	A515-50RAS
	75'	A515-75RAF	A515-75RBF	A515-75RAS
	100'	A515100RAF	A515100RBF	A515100RAS
2-1/2"	25'	A525-25RAF	A525-25RBF	A525-25RAS
	50'	A525-50RAF	A525-50RBF	A525-50RAS
	75'	A525-75RAF	A525-75RBF	A525-75RAS
	100'	A525100RAF	A525100RBF	A525100RAS

N