

Synthetic Single Jacket Mill Hose

Application

- Used in open end water discharge applications only; not intended for fire fighting service



Feature

- Consult Dixon® for pricing and availability on 75' lengths and other threads and configurations

Materials

- Outer construction: single jacket, all polyester
- Tube construction: black, PVC rubber

Specifications

- Burst pressure: **450 PSI** at 70°F (21°C)
- Proof test pressure: **300 PSI** at 70°F (21°C)
- Service test pressure: **150 PSI** at 70°F (21°C)

Coupled with NPSH Female and Male Expansion Ring Couplings

Size	Length	Part #
1-1/2"	50'	M15-50RAS
	100'	M15100RAS
2"	50'	M20-50RAS
	100'	M20100RAS
2-1/2"	50'	M25-50RAS
	100'	M25100RAS



Coupled with NST (NH) Female and Male Expansion Ring Couplings

Size	Length	Part #
1-1/2"	50'	M15-50RAF
	100'	M15100RAF
2-1/2"	25'	M25-25RAF
	50'	M25-50RAF
	100'	M25100RAF



N

Coupled with MNPT x MNPT Male Expansion Ring Couplings

Size	Length	Part #
1-1/2"	50'	M15-50RAT
	100'	M15100RAT
2"	50'	M20-50RAT
	100'	M20100RAT

