



Steel Hose Cabinet

Features

- Designed for wall installation, with or without legs, or free standing
- Supplied with holes in the back for wall mounting and 1" pipe couplings on the bottom for adding legs
- Hose, accessories, and mounting hardware not included
- Furnished without legs; HC30143-PL² (see equipment table below)



Material

- Red polyester coated finish on 18-gauge steel

Approval

- Factory Mutual approved

Steel Part

HC30143

Dimensions

Width	Depth	Height
60"	15"	48"

Basic Approved Equipment for Hose Cabinet

Examples			Quantity Required		
Part #	Description	Page #	Factory Mutual	UL and FIA	ISO
A525-50RAF ¹	2-1/2" x 50' single jacket hose	766	4	5	5
A515-50RAF ¹	1-1/2" x 50' single jacket hose	766	2	0	0
UPP250F ¹	Underwriters play pipe	806	0	2	2
BFN250NST ¹	2-1/2" adjustable fog nozzle	794	2	0	0
HA2515F ¹	2-1/2" x 1-1/2" pin lug adapter	815	1	0	0
233	universal spanner	843	4	5	5
189	adjustable hydrant wrench	844	2	2	2
PHFA6	6 lb. fire axe	865	0	1	1
FCB48	crowbar	---	0	1	1
SW150 ¹	1-1/2" hose coupling gasket	782, 783, 805, 829	4	5	5
SW250 ¹	2-1/2" hose coupling gasket	782, 783, 805, 829, 836	2	0	0
HC30143-PL ²	1" x 18" pipe leg (must order 4)	---	4	4	4

¹ Threads must be appropriate to the authority having jurisdiction

² Optional accessories

N