

## Fire Jacket for Hose

### Application

- Used to protect hose and hose assemblies, tubing, piping, wiring and cables from high temperatures, direct flame, or molten splash

### Features

- Helps maintain line temperature and reduce environmental overheating and overcooling
- Sleeving slides easily over hose and expands to go over fittings
- Resistant to hydraulic fluids and lubricating oil
- Iron oxide red color
- Supplied in 50' lengths
- Made in USA

### Material

- Compounded silicone rubber coating over fiberglass

### Specifications

- Temperature range: -65°F to 500°F (-54°C to 260°C)

### Approvals

- Completely non-asbestos, REACH - RoHS compliant
- Meets flammability requirements of UL 94 HB and UL 94 V-0

Nominal I.D.	Part #
1/4"	0610-4
3/8"	1010-6
1/2"	1310-8
5/8"	1610-10
3/4"	1910-12
7/8"	2210-14
1"	2510-16
1-1/4"	3210-20
1-1/2"	3810-24
1-3/4"	4510-28
2"	5110-32
2-1/2"	6410-40
3"	7610-48
4"	10210-64



## Fire Jacket Tape

### Application

- Used to seal the ends of fire jackets to prevent fraying and fluid wicking

### Features

- Completely non-asbestos
- Iron oxide red color
- Made in USA

### Specification

- Temperature range: -45°F to 380°F (-45°C to 200°C)

Size	Length	Silicone Rubber Part #
1"	12 yards	FTH100



## Non-Adhesive Fire Tape

### Features

- Fluid resistant to hydraulic fluids and lubricating oils
- Should be installed in a spiral wrap utilizing 30% to 50% overlap
- Iron oxide red color
- Made in the USA

### Specification

- Temperature range: -65°F to 500°F (-54°C to 260°C)

Width	Length	Fiberglass Coated Silicone Rubber Part #
3"	50'	4055-3

