

Viper® Select Gallonage Nozzles

Feature

- Four gallonage selection rings **30, 60, 90, and 125 GPM**

Material

- Constructed of E-Lite® aluminum and brass internals

Specification

- Standard operating pressure **300 PSI** maximum



Size	Thread	GPM at 100 PSI	Part #
1-1/2"	NST	30 - 125	DSG3012F
	NPSH		DSG3012S

Feature

- Four gallonage selection rings **15, 30, 50, and 60 GPM**

Size	Thread	GPM at 100 PSI	Part #
1-1/2"	NST	15 - 60	DSG1560F
	NPSH		DSG1560S

Viper Select Gallonage Low Flow Nozzles

Features

- Four gallonage selection rings **5, 10, 25, and 40 GPM**
- Available without pistol grip

Material

- Constructed of E-Lite aluminum and brass internals

Specification

- Standard operating pressure **300 PSI** maximum



Size	Thread	GPM at 100 PSI	Part #
1"	NST	5 - 40	DSG540F
	NPSH		DSG540S

Viper Constant Gallonage Nozzles

Features

- Full-time swivels and spinning teeth
- BIMATIC flush system allows flush without shutting down
- Removable pistol grip

Material

- Constructed of E-Lite aluminum and brass internals

Specification

- Standard operating pressure: **100 PSI** (optional pressures of **50** or **75 PSI**)

Approvals

- EN 15182-2 TYPE 3 certified
- NFPA 1964 Compliant



Size	Thread	GPM at 100 PSI	Part #
1-1/2"	NST	60 - 95	DVS95F
	NPSH		DVS95S
2-1/2"	NST	150 - 200	DVS250F
	NPSH		DVS250S

N