


### Thermoplastic Caps

#### Caps with Chain

**Application**

- Prevents entry of foreign material and protects male outlet threads on valves and hydrants

**Feature**

- NOT intended to be pressurized 

| Size   | Thread   | Polycarbonate Part # |
|--------|----------|----------------------|
| 1-1/2" | NPSH     | PFCW150              |
|        | NST (NH) | PFCW150F             |
| 2"     | NPSH     | PFCW200              |
| 2-1/2" | NST (NH) | PFCW250F             |
| 3"     | NST (NH) | PFCW300F             |



#### Pressurizable Cap with Chains

**Specification**

- Can be pressurized to 300 PSI

| Size   | Thread          | Polycarbonate Part # |
|--------|-----------------|----------------------|
| 2-1/2" | NST (NH) Thread | PFC250F              |



#### Hydrant Caps

**Size**

- 1-1/8" pentagonal nut with weep hole

**Feature**

- Gasket not required

| NST (NH) Thread | Polycarbonate Part # |
|-----------------|----------------------|
| 2-1/2"          | PFCW250F-Y           |
| 4"              | PFCW400F-Y           |
| 4-1/2"          | PFCW450F-Y           |




#### Universal Hose Cap

**Application**

- Universal push on – pull off cap protects all threads by gripping the valve or outlet on the inside of the waterway

**Feature**

- NOT intended to be pressurized 

| Size   | Polycarbonate Part # |
|--------|----------------------|
| 2-1/2" | PFC250U              |

