

MSA – Storz x Rigid Male

Storz x NST (NH) Male

| Storz Size | NST (NH) Male Thread | 6061-T6 Forged Aluminum Part # |
|------------|----------------------|--------------------------------|
| 1-1/2" | 1-1/2" | MSA1515F |
| 2" | 1-1/2" | MSA2015F |
| 2-1/2" | 2-1/2" | MSA2525F |
| 3" | 2-1/2" | MSA3025F |
| 4" | 2-1/2" | MSA4025F |
| | 4" | MSA4040F |
| | 4-1/2" | MSA4045F |
| 5" | 2-1/2" | MSA5025F |
| | 5" | MSA5050F |



Storz x NPT Male

| Storz Size | NPT Male Thread | 6061-T6 Forged Aluminum Part # |
|------------|-----------------|--------------------------------|
| 1-1/2" | 1-1/2" | MSA1515T |
| 2" | 1-1/2" | MSA2015T |
| 2-1/2" | 2" | MSA2520T |
| | 2-1/2" | MSA2525T |
| | 3" | MSA2530T |
| 3" | 3" | MSA3030T |
| 4" | 4-1/2" | MSA4025T |
| | 4" | MSA4040T |
| 5" | 4" | MSA5040T |
| 6" | 6" | MSA6060T |



Storz x NPSH Male

| Storz Size | NPSH Male Thread | 6061-T6 Forged Aluminum Part # |
|------------|------------------|--------------------------------|
| 1-1/2" | 1-1/2" | MSA1515S |
| 2" | | MSA2015S |



1-1/2" x 1-1/2"



SLSA – Storz Live Swivel

Specification

- Working pressure: 200 PSI at 70°F (21°C)

| Storz | FNPT | 6061-T6 Forged Aluminum Part # |
|-------|------|--------------------------------|
| 4" | 4" | SLSA4040T |
| 5" | | SLSA5040T |



NOTE: Optional configurations from 2-1/2" to 6" on the non-storz side.