



Reversible Concealed Angle Siamese Body

Application

- Stainless steel FDC provides water up to 90 stories without auxiliary pumping systems

Sizes

- Bodies: 4" and 6"
- Snoots: 2-1/2" x 2-1/2" and 2-1/2" x 3"

Features

- Uniquely designed clappers are fully reversible with perpendicular trunnion, allowing one body to be installed for top or bottom connections
- Concealed unit mounts behind a wall plate; escutcheon for exposed installation sold separately

Materials

- Body: 316 stainless steel
- Shutters: 4" x 2-1/2": brass
6" x 3": 316 stainless steel
- Snoots: 316 stainless steel
- Pivot pins: brass on concealed units, stainless steel on exposed units

Specifications

- 4" x 2-1/2" maximum working pressure: **500 PSI**
- 6" x 3" maximum working pressure: **600 PSI**

Approvals

- 4" x 2-1/2" is FM Approved
- 6" x 3" is FM and New York Fire Department approved



4" X 2-1/2"
unpolished



6" X 3"
unpolished



6" X 3"
polished

Outlet	(2) Inlets	Description	Stainless Steel Part #
4" NPT	2-1/2" NPT	concealed angle body	4025REV90SS
6" grooved	3" NPT	concealed straight body	DCS6030GSS
6" NPT	3" NPT	concealed or exposed angle body	90CREV6030SS
		concealed or exposed angle body polished	90CREV6030SS-P
6" NPT	3" NPT	reversible NYFD fire department connection assembly for exposed installation with proper identification plate (not included). Customer may choose from open snoots below for alternatives. Contact Dixon® for part number	90CREV6030SSPAT

Open Snoots

Swivel	NPT Thread	PSI	Stainless Steel Female Part #	Stainless Steel Male Part #
2-1/2" NST (NH)	2-1/2"	500	SF250FSS	SM250FSS
	3"	600	SF2530FSS	SM2530FSS
3" NST (NH)	3"	600	SF300FSS	SM300FSS
3" NYFD	3"	600	SF300NYFDSS	SM300NYFDSS



2-1/2" x 3" male
polished satin



3" x 3" male
polished satin

N