

Type C Couplers Coupler and Hose Shank

Features

- Supplied with EPDM gaskets, 304 stainless steel handles and pins
- 1/2" couplers and adapters will interchange with 3/4" couplers and adapters, only the threads and barbs are 1/2"
- 1-1/4" couplers and adapters will interchange with 1-1/2" couplers and adapters, only the threads and barbs are 1-1/4"
- Replacements: gasket use EPR on page 69, pull rings use R200SS on page 72, safety clip use GSAFETYCLIP on page 83
- NOT recommended for use with PTFE gaskets, polypropylene cam & groove should not be mixed with metal fittings



Specification

- Maximum operating pressure: **125 PSI** (1/2" - 1"), **100 PSI** (1-1/4" - 2"), **60 PSI** (3"), and **50 PSI** (4"); recommendations based on the use of mating Dixon® fittings at an ambient temperature of **70°F (21°C)** with standard seal installed

| Size | Glass-Filled Polypropylene Part # | Optional Qty |
|-----------------|-----------------------------------|--------------|
| 3/4" x 1/2" | PPC50 | 24 |
| 3/4" | PPC75 | 24 |
| 1" | PPC100 | 24 |
| 1-1/2" x 1-1/4" | PPC125 | 24 |
| 1-1/2" | PPC150 | 24 |
| 2" | PPC200 | 24 |
| 3" | PPC300 | 24 |
| 4" | PPC400 ¹ | 8 |

¹ 4" coupler has 4 handles

Type D Couplers Coupler and Female NPT

Features

- Supplied with EPDM gaskets, 304 stainless steel handles and pins
- 1/2" couplers and adapters will interchange with 3/4" couplers and adapters, only the threads and barbs are 1/2"
- 1-1/4" couplers and adapters will interchange with 1-1/2" couplers and adapters, only the threads and barbs are 1-1/4"
- Replacements: gasket use EPR on page 69, pull rings use R200SS on page 72, safety clip use GSAFETYCLIP on page 83
- NOT recommended for use with PTFE gaskets, polypropylene cam & groove should not be mixed with metal fittings



Specification

- Maximum operating pressure: **125 PSI** (1/2" - 1"), **100 PSI** (1-1/4" - 2"), **60 PSI** (3"), and **50 PSI** (4"); recommendations based on the use of mating Dixon fittings at an ambient temperature of **70°F (21°C)** with standard seal installed

| Size | Glass-Filled Polypropylene Part # | Optional Qty |
|-----------------|-----------------------------------|--------------|
| 3/4" x 1/2" | PPD50 | 24 |
| 3/4" | PPD75 | 24 |
| 1" | PPD100 | 24 |
| 1-1/2" x 1-1/4" | PPD125 | 24 |
| 1-1/2" | PPD150 | 24 |
| 2" | PPD200 | 24 |
| 3" | PPD300 | 24 |
| 4" | PPD400 ¹ | 8 |

¹ 4" coupler has 4 handles