

### 1/4 Turn Ball Wye Valve



**Features**

- Rocker lug swivel
- Operates easily under high pressure
- Handles are not field replaceable
- Seals on the ball are field adjustable and field replaceable

**Specification**

- Maximum operating pressure: **250 PSI** (water only) at **70°F (21°C)**

**Approval**

- Meets NSN specifications # 4210-00-255-0234

Inlet Female	(2) Outlets Male	Cast Brass Part #
2-1/2" NST (NH)	1-1/2" NPSH	S7337S <sup>1</sup>
	1-1/2" NST	S7337F <sup>1</sup>

<sup>1</sup> Domestic

### Full Flow 1/4 Turn Ball Wye Valves

**Application**

- Recommended for charged pre-connected hose lines

**Features**

- Pin lug swivel
- Other configurations are available, contact Dixon® for additional information



**Specification**

- Maximum operating pressure: **175 PSI** (water only) at **70°F (21°C)**

Inlet Female Swivel	(2) Outlets Male	Cast Brass Part #
1-1/2" NPSH	1-1/2" NPSH	S7100-15S
1-1/2" NST (NH)	1-1/2" NST (NH)	S7100-15
2-1/2" NST (NH)		S7100

### Leader Line 1/4 Turn Ball Wye Valve

**Feature**

- Body painted red with chrome trim

**Specification**

- Maximum operating pressure: **300 PSI** (water only) at **70°F (21°C)**



Inlet Female NST (NH)	(2) Outlets Male NST (NH)	Brass Part #
2-1/2"	1-1/2"	LLBV2515F

N