

NPT Threaded Bell Reducers



150# 316 stainless steel



3000# forged steel



125# brass

Features

- Other sizes available
- 304 stainless steel fittings are also available; consult Dixon® for pricing and availability

Female NPT	Female NPT	150# 316 Stain.Steel Part #	3000# Forged Steel Part #	125# Brass Part #
1/4"	1/8"	---	---	---
3/8"	1/8"	---	---	---
	1/4"	BR3825SS	---	---
1/2"	1/4"	BR5025SS	---	---
	3/8"	BR5038SS	BR5038FS	BR5038B
3/4"	3/8"	BR7538SS	---	---
	1/2"	BR7550SS	BR7550FS	BR7550B
1"	1/2"	BR1050SS	---	BR1050B
	3/4"	BR1075SS	BR1075FS	BR1075B
1-1/4"	1"	BR1210SS	---	BR1210B
	3/4"	---	---	BR1575B
1-1/2"	1"	BR1510SS	BR1510FS	BR1510B
	1-1/4"	BR1512SS	BR1512FS	---
2"	1"	BR2010SS	BR2010FS	BR2010B
	1-1/2"	BR2015SS	BR2015FS	BR2015B
2-1/2"	2"	---	---	BR2520B
3"	2"	BR3020SS	---	BR3020B
4"	3"	---	---	BR4030B

Adapters

Reducer Couplings

Feature

- Ref SAE 130138



Female NPTF	Brass		Opt Qty	Lead-Free Brass ^{1,2} Part #	Opt Qty
	Previous Part #	Part #			
1/4" x 1/8"	RC2F1F	3770402C	50	---	---
3/8" x 1/8"	RC3F1F	3770602C	50	---	---
3/8" x 1/4"	RC3F2F	3770604C	50	---	---
1/2" x 1/4"	RC4F2F	3770804C	25	---	---
1/2" x 3/8"	RC4F3F	3770806C	10	3770806CLF	10
3/4" x 3/8"	RC6F3F	3771206C	10	---	---
3/4" x 1/2"	RC6F4F	3771208C	10	3771208CLF	10
1" x 1/2"	---	3771608C	10	---	---
1" x 3/4"	---	3771612C	10	---	---

¹ NSF®/ANSI 61 certified Lead-Free Brass <=0.25% lead, Alloy C2745

² Conforms To: Safe Water Drinking Act (SWDA) of Jan. 4, 2014; California AB1953; RoHS Compliant

NOTE: NPTF threads

NOTE: For additional information on pipe dimensions, please reference dixonvalve.com.