

Reducer Hex Bushings

Feature

- Ref SAE 130140

Male NPTF	Female NPTF	Brass		Opt Qty	Lead-Free Brass ³ Part #	316 Stainless Steel ⁴ Part #	Opt Qty
		Previous Part #	Part #				
1/4"	1/8"	HB1F2M	3730402C	100	3730402CLF ²	3730402SS	100
3/8"	1/8"	HB1F3M	3730602C	100	---	3730602SS	25
	1/4"	HB2F3M	3730604C	100	3730604CLF ²	3730604SS	25
1/2"	1/8"	HB1F4M	3730802C	25	---	3730802SS	25
	1/4"	HB2F4M	3730804C	50	3730804CLF ²	3730804SS	50
	3/8"	HB3F4M	3730806C	50	3730806CLF ²	3730806SS	50
3/4"	1/8"	HB1F6M	3731202C ¹	25	---	---	25
	1/4"	HB2F6M	3731204C	25	3731204CLF ⁵	3731204SS	25
	3/8"	HB3F6M	3731206C	25	3731206CLF ⁵	3731206SS	25
	1/2"	HB4F6M	3731208C	25	3731208CLF ²	3731208SS	25
1"	1/4"	HB2F8M	3731604C ¹	10	---	3731604SS	10
	3/8"	HB3F8M	3731606C ¹	10	3731606CLF ^{4,5}	3731606SS	10
	1/2"	HB4F8M	3731608C	10	3731608CLF ^{4,5}	3731608SS	10
	3/4"	HB6F8M	3731612C	10	3731612CLF ^{4,5}	3731612SS	10



brass



316 stainless steel

- ¹ SAE does not provide a standard for these sizes
- ² NSF®/ANSI 61 certified lead-free brass <=0.25% lead, Alloy C2745
- ³ Conforms To: Safe Water Drinking Act (SWDA) of Jan. 4, 2014; California AB1953; RoHS Compliant
- ⁴ NPT thread
- ⁵ Lead-free per NSF72


Adapters

Female NPTF x Male NPTF

Feature

- Ref SAE 130139

Female NPTF	Male NPTF	Brass		Opt Qty	Lead-Free Brass ^{1,2} Part #	316 Stainless Steel ³ Part #	Opt Qty
		Previous Part #	Part #				
1/8"	1/8"	RA1F1M	3750202C	100	---	---	---
1/4"	1/8"	RA2F1M	3750402C	50	3750402CLF	3750402SS	50
	1/4"	RA2F2M	3750404C	50	3750404CLF	3750404SS	50
3/8"	1/8"	RA3F1M	3750602C	50	---	3750602SS	50
	1/4"	RA3F2M	3750604C	50	---	3750604SS	50
	3/8"	RA3F3M	3750606C	50	---	3750606SS	50
1/2"	1/4"	RA4F2M	3750804C	25	---	3750804SS	25
	3/8"	RA4F3M	3750806C	25	---	3750806SS	25
	1/2"	RA4F4M	3750808C	25	3750808CLF	3750808SS	10
3/4"	3/8"	RA6F3M	3751206C	10	---	3751206SS	10
	1/2"	RA6F4M	3751208C	10	---	3751208SS	10
	3/4"	RA6F6M	3751212C	10	3751212CLF	3751212SS	10
1"	1/2"	---	3751608C	5	---	3751608SS	5
	3/4"	---	3751612C	5	---	3751612SS	5
	1"	---	---	---	---	3751616SS	5



brass



316 stainless steel

- ¹ NSF®/ANSI 61 certified Lead-Free Brass <=0.25% lead, Alloy C2745
- ² Conforms To: Safe Water Drinking Act (SWDA) of Jan. 4, 2014; California AB1953; RoHS Compliant
- ³ Threads are NPT

NOTE: For additional information on pipe dimensions, please reference dixonvalve.com.