

Bulkhead Fittings

Applications

- For use on most poly storage tanks and many steel and fiberglass tanks

Features

- Glass reinforced polypropylene provides strength and chemical resistance
- EPDM gaskets are standard
- FKM gaskets are available; contact Dixon® to order



63931



63481



63683

Female NPT Fittings

Female NPT	Hole Size	Polypropylene Part #
1/2"	1-7/16"	62834
3/4"	1-7/16"	60401
1"	2-1/4"	60427
1-1/4"	2-1/4"	60403
1-1/2"	3"	60124
1-1/2"	2-3/8"	63931 ¹
2"	3"	60405
2"	3"	63481 ²
2" HD ³	3-1/4"	63683
3"	4-1/2"	62299 ¹

¹ 1-1/2" and 3" do not contain a washer

² Designed for tank wall thickness less than 3/8" – low profile

³ Heavy duty version

Gaskets

Size	EPDM Part #
1/2" - 3/4"	60402
1" - 1-1/4"	60404
1-1/2"	63938
2"	60406
2" ¹	60336
3"	60331

¹ Heavy duty



Bulkhead Couplings

Application

- Used to connect a tube or housing through a wall or other barrier



brass



316 stainless steel

Female NPTF	External Male UNS	Brass Part #	Brass Length	316 Stainless Steel ¹ Part #	Stainless Steel Length
1/8"	5/8"	207BH2	1.50"	207BH2SS	1.50"
1/4"	3/4"	207BH4	1.50"	207BH4SS	1.02"
1/4"	3/4"	207BH4S	.94"	---	---
3/8"	1"	207BH6	1.31"	207BH6SS	1.31"
1/2" x 3/8"	1-1/8"	207BH8-6	1.50"	---	---
1/2"	1-1/8"	207BH8	1.50"	207BH8SS	1.50"
3/4"	1-5/16"	207BH12	1.50"	207BH12SS	1.50"
1"-11-1/2"	1-5/8"-14	---	1.68"	207BH16SS	1.68"

¹ NPT threads

NOTE: Brass part contains 12L14 steel washer nut; 316 stainless steel part contains FKM seal gasket.