

Hammer Unions 400-Series



Feature

- Red sub, black nut

Specification

- Used on manifold and line connections, pump, suction, and mud service up to **4,000 PSI** NSCWP (non-shock cold working pressure)

Size	Configuration	Forged Steel Part #
2"	threaded	HU400200
3"		HU400300
4"		HU400400

602-Series

Features

- Lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- Orange sub, black nut

Specification

- For use in mud, manifold service and truck mounting applications running water, oil or mud service up to **6,000 PSI** NSCWP



Size	Configuration	Forged Steel Part #
1"	threaded	HU602100
2"	threaded	HU602200
3"	threaded	HU602300
	butt weld	HU602300BW ¹
4"	threaded	HU602400

¹ Butt weld ends are schedule 80


1002-Series

Features

- Lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- Blue sub, red nut

Specification

- For use in high pressure systems for choke and kill lines, cementing, and acidizing up to **10,000 PSI** NSCWP



Size	Configuration	Forged Steel Part #
1"	threaded	HU1002100
2"	threaded	HU1002200
3"	threaded	HU1002300
	butt weld	HU1002300BW ¹
4"	threaded	HU1002400
	butt weld	HU1002400BW ¹

¹ Butt weld ends are schedule XXS

