

Stainless Steel Liquid Filled Gauges

Application

- Designed for severe service applications, providing the corrosion resistance and durability of a permanently sealed gauge

Features

- ± 2-1-2% accuracy
- 1/4" NPT lower mount stainless connector

Materials

- Polycarbonate window
- 304 stainless case and crimp ring
- Glycerin filled

Specification

- Ambient temperature range: -4°F to 140°F (-20°C to 60°C)

F



GLSS1500

PSI Range	Figure Interval	Minor Gradient	2-1/2" Face 1/4" Lower Mount Part #
0-15	3	.2	GLSS15
0-30	5	.5	GLSS30
0-60	10	1	GLSS60
0-100	20	2	GLSS100
0-160	20	2	GLSS160
0-200	50	5	GLSS200
0-300	50	5	GLSS300
0-400	100	10	GLSS400
0-600	100	10	GLSS600
0-1000	200	20	GLSS1000
0-1500	300	20	GLSS1500
0-2000	500	50	GLSS2000
0-3000	500	50	GLSS3000
0-5000	1000	100	GLSS5000
0-10000	2000	200	GLSS10000

All Stainless Steel Liquid Filled Gauges

Application

- Designed for severe service applications, providing the corrosion resistance and durability of a permanently sealed gauge

Features

- ± 2-1-2% accuracy
- 1/4" NPT center back mount stainless connector

Materials

- Polycarbonate window
- 304 stainless case and crimp ring
- Glycerin filled

Specification

- Ambient temperature range: -4°F to 140°F (-20°C to 60°C)



PSI Range	Figure Interval	Minor Gradient	2-1/2" Face 1/4" Center Back Mount Part #
0-100	20	2	GLSSC100
0-160	20	2	GLSSC160
0-200	50	5	GLSSC200