

## EZ Boss-Lock Type C Couplers with Collared Hose Shank

### Coupler x Collared Hose Shank

#### Features

- Design provides greater resistance to end pull than conventional band clamps and is intended for use with Strap-Grip saddles
  - saddles are sold in pairs and designed for use with 3/4" or 5/8" wide band clamps
  - bands must be purchased separately
- Band clamps should first be applied to the O.D. to seal the hose, then Strap-Grip saddles should be banded over the initial clamp to anchor the fitting in the hose

| Size   | 316 Stainless Steel<br>Part # |
|--------|-------------------------------|
| 1"     | RC100CEZ                      |
| 1-1/2" | RC150CEZ                      |
| 2"     | RC200CEZ                      |




B

## Boss-Lock Type C Couplers with Notched Shank

### Coupler x Hose Shank


#### Features

- Coupling can be removed from a damaged hose by cutting away the ferrule, without necessarily damaging the fitting, after inspection of the fitting to determine its suitability for reuse, it can be reinstalled into another hose by using a new ferrule
- System allows you to better manage your inventories, you can stock one coupling and two ferrules, and cover the same hose range with less inventory, you must purchase a fitting and the matching ferrule to create an assembly
- For use with notched ferrules on page 45


Dixon® stems and ferrules are specifically designed to be used together as a coupling system. Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturers' stems or ferrules with Dixon products. 

| Size   | 316 Stainless Steel<br>Part # |
|--------|-------------------------------|
| 1-1/2" | RC150BLNO                     |
| 2"     | RC200BLNO                     |
| 3"     | RC300BLNO                     |
| 4"     | RC400BLNO                     |

NOTE: Contact Dixon for swage and crimp recommendations.



crimped assembly



swaged assembly