

Dixon® Vapor Recovery Couplers

C

Feature

- Not intended for liquid service; for vapor recovery only



Materials


- Body: cast aluminum
- Arms: bronze with stainless steel pins
- Finger rings: plated carbon steel
- Gasket: nitrile rubber



Coupler with Probe and Adapter


Coupler Size	Adapter Size	356T6 Aluminum Part #
4"	3"	4030-DAVR-AL

Coupler with Probe and Coupler with Probe



Coupler Size	Coupler Size	356T6 Aluminum Part #
4"	4"	400-DDVR-AL

Coupler with Probe and Hose Shank



VR4030CS-AL

Applications

- For use with 3" vapor hose
- Not intended for liquid service; for vapor recovery only



Features

- VR4030CS-AL has an FKM O-ring poppet seal
- Dixon replacement handle assemblies will not work on these fittings; contact Dixon for replacements



Materials

- Cast aluminum body
- Arms : bronze
- Pins and finger rings: stainless steel
- Gasket: nitrile rubber



VRC3000AL

Coupler Size	Hose Shank Size	Description	Part #
3"	3"	---	VRC3000AL
4"	2"	---	4020-CVR-AL
4"	3"	no poppet	4030-CVR-AL
4"	3"	poppet	VR4030CS-AL <sup>1</sup>
4"	3"	floating bridge poppet	VR4030CS-SH <sup>2</sup>
4"	4"	no poppet	400-CVR-AL
4"	4"	floating bridge poppet	VR4040CS-AL <sup>2</sup>

<sup>1</sup> Interchanges with all competitor vapor valves except Civacon #633LVH (special bulb design)

<sup>2</sup> Superior interface with air interlock



4030-CVR-AL

Repair Kits

Description	Part #
seal repair kit: gasket, machine screw and FKM O-ring	VR4040CSRK1
cam arm repair kit: paddle arm and cam arm pin	VR4040CSRK2