

## Vent-Lock® Safety Cam & Groove Couplings

### Accessories

#### Dixon® Handle Assemblies

##### Features

- Use only with Dixon® Vent-Lock couplers
- Includes handle, ring, and pin




Size	316 Stainless Steel Part #
1"	L100-HSCRPI-SI
1-1/2" - 2"	L200-HSCRPI-SI

#### EZ Boss-Lock Handle Assemblies

##### Features

- Use only with EZ Boss-Lock Vent-Lock couplers
- Includes handle, ring, and pin



Size	316 Stainless Steel Part #
1"	LRHEZ175
1-1/2" - 2"	LRHEZ152
3"	LRHEZ34

## Cast Steel Industrial Valves 150 Lb.

##### Features

- Bolted bonnet
- MTRs available

##### Specifications

- End configuration: raised face (RF)
- Basic design: API 600 – Gate valve  
API 623 – Globe valve  
API 594 – Check valve
- End flange: ASME B16.5
- Face to face: ASME B16.10

##### Materials

- Body and bonnet made from cast A216 WCB
- Gasket: 304 stainless steel and graphite



#### Gate Valve

Part #	Size	Class	Ends	API Trim	Weight (lbs)	Cv (gpm)
D861008-300	3"	150	RF	8	64	109.7
D861008-400	4"	150	RF	8	87	190.0
D861008-600	6"	150	RF	8	149	427.5
D861008-800	8"	150	RF	8	229	759.8



#### Globe Valve

Part #	Size	Class	Ends	API Trim	Weight (lbs)	Cv (gpm)
D851008-300	3"	150	RF	8	82	116.5
D851008-400	4"	150	RF	8	126	182.1
D851008-600	6"	150	RF	8	197	409.6
D851008-800	8"	150	RF	8	325	728.2



#### Check Valve

Part #	Size	Class	Ends	API Trim	Weight (lbs)	Cv (gpm)
D891008-300	3"	150	RF	8	51	108.4
D891008-400	4"	150	RF	8	85	197.9
D891008-600	6"	150	RF	8	134	445.2
D891008-800	8"	150	RF	8	227	799.4