


Global Air King®

Features

- Supplied with safety clip and rubber washers
- Use with Boss® clamps; see pages 167-168
- Not to be used for steam service 
- Must use safety clips, safety clips are same size for both 2-lug and 4-lug Air King couplings, see page 196

Specification

- Pressure rating: **150 PSI** at ambient temperature **70°F (21°C)**

2-Lug Hose Ends



Size	Plated Steel Part #	Pkg Qty	Brass Part #	Pkg Qty
3/8"	GAMH	50	GABH	50
1/2"	GAM1	50	GAB1	25
3/4"	GAM6	50	GAB6	50
1"	GAM11	50	GAB11	50

Global 2-Lug Hose End with Ferrule



Size	Plated Steel Part #	Pkg Qty
3/4"	GAM6WF	25

2-Lug Male NPT Ends



Size	Plated Steel Part #	Brass Part #	Pkg Qty
1/2"	GAM2	GAB2	50
3/4"	GAM7	GAB7	50
1"	GAM12	GAB12	50

2-Lug Female NPT Ends



Size	Plated Steel Part #	Brass Part #	Optional Qty
1/2"	GAM3	GAB3	25
3/4"	GAM8	GAB8	50
1"	GAM13	GAB13	50

2-Lug Blank End



Plated Steel Part #	Brass Part #	Optional Qty
GAM0	GAB0	25

2-Lug Triple Connection



Plated Steel Part #	Brass Part #	Optional Qty
GAM10	GAB10	25

NOTE: Air King is for air and water service only. Warning: Never use any Air King coupling for steam service! None of Dixon's catalog information is to be interpreted to mean that this type of coupling is suitable for use on steam hose. 