


U-Series Universal Pneumatic Couplings

Features

- Couplers are automatic
- 2U-Series 6-in-1 (ARO 210, Industrial, Tru-Flate, Lincoln, Italian, and CEJN 320)
- 3U-Series 4-in-1 (ARO 310, Industrial, Tru-Flate, and CEJN 410)
- Parker UC-Series, Hansen Auto-Flo 23, and Coilhose Series US
- Although the universal coupler permits multiple series nipples to mate with one coupler, it is recommended to match like series couplers and nipples. When using a universal coupler, the lower performance rating between the coupler and nipple must take precedence
- Some pneumatic applications require the pressurized air to be 'dried' to ensure proper operation of equipment and/or application of product (i.e. auto body shops); it is best to match like series couplers and nipples in these applications. If it is necessary to use a universal coupler, lube the seal and valve area regularly to ensure reliable service.
- For air service only 

Specification

- Temperature range: -40°F to 250°F (-40°C to 121°C)

Female Threaded Couplers

Body Size	Threads	Brass Part #
1/4"	1/4" – 18 NPT	2UF2-B
	1/4" – 19 BSPP	2UBF2-B
	3/8" – 18 NPT	2UF3-B
	3/8" – 19 BSPP	2UBF3-B
3/8"	3/8" – 18 NPT	3UF3-B
	3/8" – 19 BSPP	3UBF3-B



Male Threaded Couplers

Body Size	Threads	Brass Part #
1/4"	1/4" – 18 NPT	2UM2-B
	1/4" – 19 BSPP	2UBM2-B
	3/8" – 18 NPT	2UM3-B
	3/8" – 19 BSPP	2UBM3-B
3/8"	3/8" – 18 NPT	3UM3-B
	3/8" – 19 BSPP	3UBM3-B



Standard Hose Barb Couplers

Body Size	Hose I.D.	Brass Part #
1/4"	1/4"	2US2-B
	3/8"	2US3-B
3/8"	3/8"	3US3-B



Push-On Hose Barb Couplers

Body Size	Hose I.D.	Brass Part #
1/4"	1/4"	2UB2-B
	3/8"	2UB3-B

