

Air Chief Automotive Interchange Couplings

Features


- Couplers are semi-automatic
- Interchange with popular makes of automotive quick-connect fittings such as Amflo®, Dill®, Milton®, and Tru-Flate®. Some designs do not interchange with others; if you plan to interchange these couplings, make sure you have plug ends with the proper configuration.

Specifications

- Pressure rating: 300 PSI
- Temperature range: -40°F to 250°F (-40°C to 121°C)

Semi-Automatic

Female Threaded Couplers



Body Size	Female NPT	Flow Rating at 100 PSI	Brass Part #	Steel Part #
1/4"	1/8"	37 CFM	DC221	---
	1/4"		DC2	---
	3/8"		DC223	---
3/8"	1/4"	70 CFM	---	DC8
	3/8"		---	DC6
	1/2"		---	DC624

Male Threaded Couplers



Body Size	Male NPT	Flow Rating at 100 PSI	Brass Part #	Steel Part #
1/4"	1/8"	37 CFM	DC101	---
	1/4"		DC1	---
	3/8"		DC103	---
3/8"	1/4"	70 CFM	---	DC7
	3/8"		---	DC5
	1/2"		---	DC504

Standard Hose Barb Couplers




Body Size	Hose I.D.	Flow Rating at 100 PSI	Brass Part #	Steel Part #
1/4"	1/4"	37 CFM	DC242	---
	3/8"		DC244	---
3/8"	3/8"	70 CFM	---	DC644
	1/2"		---	DC645

Push-On Hose Barb Couplers



Body Size	Hose I.D.	Flow Rating at 100 PSI	Brass Part #	Steel Part #
1/4"	1/4"	37 CFM	DC242L	---
	3/8"		DC244L	---
3/8"	3/8"	70 CFM	---	DC644L

Air Chief Automotive Actual Size Profile Charts



E