

## Air Brake Fittings

### Inserts

**Feature**

- For SAE J844 tubing



| Tube Size | 302 or 304 Stainless Steel Part # | Pkg Qty |
|-----------|-----------------------------------|---------|
| 1/4"      | 63NAB4                            | 200     |
| 3/8"      | 63NAB6                            | 200     |
| 1/2"      | 63NAB8                            | 100     |
| 5/8"      | 63NAB10                           | 100     |
| 3/4"      | 63NAB12                           | 100     |

### Nuts

**Feature**

- Ref. SAE 100110



| Tube Size | Male NPT    | Part #  | Pkg Qty |
|-----------|-------------|---------|---------|
| 3/16"     | 5/16" - 24  | 61NAB3  | 100     |
| 1/4"      | 7/16" - 24  | 61NAB4  | 100     |
| 3/8"      | 17/32" - 24 | 61NAB6  | 100     |
| 1/2"      | 11/16" - 20 | 61NAB8  | 50      |
| 5/8"      | 13/16" - 18 | 61NAB10 | 25      |
| 3/4"      | 1" - 18     | 61NAB12 | 25      |

## Air Brake Fittings for Rubber Hose

**Application**

- For use with SAE J1402 air brake hose in making hose assemblies

**Feature**

- Will meet DOT FMVSS 571-106 standards when used with SAE J1402 air brake hose

**Specifications**

- Working pressure: up to 225 PSI
- Temperature: -50°F to 212°F (-46° to 100°C)

**Assembly Guide**

1. Slide nut onto hose
2. Slide sleeve onto hose with tapered edge toward fitting body
3. Firmly bottom the hose into fittings
4. Screw nut onto body until it contacts the fittings body's hex

### Hose Springs



| Hose Size | Length | Brass Alloy 360 Part # |
|-----------|--------|------------------------|
| 3/8"      | 2.70"  | 56RBSG-06              |
| 1/2"      | 2.70"  | 56RBSG-08              |

### Spring Guard Nuts



| Hose Size | Straight Thread | Brass Alloy 360 Part # |
|-----------|-----------------|------------------------|
| 3/8"      | 31/32" - 20     | 61RBSG-06              |
| 1/2"      | 1-3/32" - 20    | 61RBSG-08              |

E