



Nickel-Plated Brass Legris® Push-In Fittings

Applications

- Push-to-connect forged fittings are nickel-plated and have an FKM seal making them suitable to use with compressed air, grease, lubricant, water
- Fittings are plated with a high phosphorous FDA nickel plate allowing them to be used in applications where exposure to harsh environments is present
- Applications include: food process, coffee machines, in-plant automotive, medical equipment, printing, misting, welding robots

Features

- FDA compliant
- Vacuum capability: 28" HG maximum circuit pressure (depends on media, temperature and diameter of tube used)
- Full flow
- Excellent resistance to abrasion and corrosion
- Silicone free
- Available in fractional and metric sizes

Specifications

- Temperature range: **-4°F to 302°F (-20°C to 150°C)**
- Pressure range: up to **435 PSI, 290 PSI: 3609, 3699 series**

Construction

- Body, backup washer, collet: high phosphorous FDA nickel-plated brass
- Seal: FKM

Male Connectors



Tube O.D.	Male NPT	Nickel-plated Brass Part #	Optional Qty
5/32"	10-32 ¹	36010420	10
	1/8"	36750411	10
1/4"	10-32 ¹	36015620	10
	1/8"	36755611	10
	1/4"	36755614	10
	3/8"	36755618	10
3/8"	1/8"	36756011	10
	1/4"	36756014	10
	3/8"	36756018	10
	1/2"	36756022	10

¹ UNF – Straight thread, supplied with gasket and plastic button

Female Connectors



Tube O.D.	Female NPT	Nickel-plated Brass Part #	Optional Qty
5/32"	1/4"	36150414	10
1/4"	1/8"	36155611	10
	1/4"	36155614	10
3/8"	3/8"	36156018	10

Equal Unions



Tube O.D.	Nickel-plated Brass Part #	Optional Qty
5/32"	36060400	10
1/4"	36065600	10
1/2"	36066200	10