


Valves

Button



Thread	Brass Part #
1/4" NPT female	BV2F
1/4" NPT male	BV2M

Tank Filler

Applications

- Used on compressed air tanks and other applications

Feature

- Standard valve stem thread



TFV1S

TFV2



TFV1L

TFV2HB

Connection	Length	Nickel Plated Part #	Length	Brass Part #
1/8" NPT	.85"	TFV1S	---	---
	1.24"	TFV1L	---	---
1/4" NPT	1"	TFV2	---	---
1/4" barb	---	---	1.57"	TFV2HB

Brass Lever External Drains

Application

- For air service only 

Specification

- Maximum operating pressure: **30 PSI** at ambient temperature **70°F (21°C)**



Female NPT	Male NPT	Brass Part #
1/4"	1/4"	LDC2



Male NPT	Male NPT	Brass Part #
1/4"	1/4"	LDCM2



Female NPT	Female NPT	Brass Part #
1/4"	1/4"	LDCF2

Brass External Drain Cocks

Application

- Designed for low pressure water and air applications

Specification

- Maximum operating pressure: **150 PSI** at ambient temperature **70°F (21°C)**
- Temperature range: **-65°F to 250°F (-54°C to 121°C)**



D02

NPT Size	Brass Part #
1/8"	D02
1/4"	D04