

### Ball Swivels



**Features**


- Brass and hardened steel construction
- O-ring seals
- Wobble action for increased flexibility with air driven tools
- Full flow at any angle, range of motion 20° to 25°

Hose Size	Male NPT	Part #	Optional Qty
1/4"	1/4"	D444S	25
3/8"	1/4"	D446S	25

### In-Line Swivels

F

**Features**

- For air service only
- Heavy-duty, free turning steel swivel 




**Specification**

- Rated to **250 PSI** at ambient temperature **70°F (21°C)**, minimum **35 PSI**

Male NPT	Female NPT	Steel Part #
3/8"	1/2"	SV17
1/2"	1/2"	SV20
3/4"	3/4"	SV26

**Feature**

- For air service only 



**Specification**

- Rated to **150 PSI** at ambient temperature **70°F (21°C)**

Male NPT	Female NPT	Brass Part #
1/4"	1/4"	D344R
3/8"	3/8"	D366R

### Air Tool Swivels



D344U



D346U, D348U

**Features**

- Swivels 360° at two pivot points allowing the air hose to drop directly to the floor
- Do not use with percussion tools 
- No flow control

**Specification**

- Rated to **150 PSI** at ambient temperature **70°F (21°C)**

NPT Size	Aluminum Part #
1/4"	D344U <sup>1</sup>
3/8"	D346U
1/2"	D348U

<sup>1</sup> D344U is a non-marring composite.