

Wilkerson® FRLs

D18-Series Combination Units

Features

- Light weight, ready-to-mount assembly comes standard with pressure gauge and modular T-bracket/joiner assembly
 - Components integrated into single unit
 - Modern design and appearance
 - Quick disconnect bowl/bowl guard
 - 5 micron element
 - 4 oz. bowl/lubricator
- Regulator:
- **0-125 PSI** adjusting range
 - Self-relieving
 - Supplied with gauge
 - 1.72 oz. bowl/filter

Specifications


- Maximum operating conditions:
 - transparent bowl: **150 PSIG (10.3 bar)** and **-13°F to 125°F (-25°C to 52°C)**
 - metal bowl: **250 PSIG (17.2 bar)** and **-13°F to 150°F (-25°C to 66°C)**

Size	Flow (SCFM)	Transparent Bowl and Guard		Metal Bowl/Sight Gauge	
		Manual Drain Part #		Manual Drain Part #	
1/2"	90	D18-04M		D18-04MMB	

NOTE: SCFM ratings at **145 PSIG** inlet pressure.



with transparent bowl and guard



D28-Series Combination Units

Features

- Light weight, ready-to-mount assembly comes standard with pressure gauge and modular T-bracket/joiner assembly
 - Components integrated into single unit
 - Modern design and appearance
 - Quick disconnect bowl/bowl guard
 - 5 micron element
 - 6 oz. bowl/lubricator
- Regulator:
- **0-125 PSI** adjusting range
 - Self-relieving
 - Supplied with gauge
 - 2.87 oz. bowl/filter


Specifications

- Maximum operating conditions:
 - 250 PSIG (17.2 bar)** and **-13°F to 125°F (-25°C to 52°C)**

Size	Flow (SCFM)	Metal Bowl/Sight Gauge	
		Manual Drain Part #	
1/2"	110	D28-04MMB	
3/4"	150	D28-06MMB	



with metal bowl



NOTE: SCFM ratings at **145 PSIG** inlet pressure.

FRLs are designed for air service only, unless otherwise indicated.

