

### Stainless Steel Liquid Filled Gauges

**Application**

- Designed for severe service applications, providing the corrosion resistance and durability of a permanently sealed gauge

**Features**

- ± 2-1-2% accuracy
- 1/4" NPT lower mount stainless connector

**Materials**

- Window: polycarbonate
- Case and crimp ring: 304 stainless
- Glycerin filled

**Specification**

- Ambient temperature range: 20°F to 158°F (-7°C to 70°C)

F



GLSS2000

PSI Range	Figure Interval	Minor Gradient	2-1/2" Face 1/4" Lower Mount Part #
0-15	3	.2	GLSS15
0-30	5	.5	GLSS30
0-60	10	1	GLSS60
0-100	20	2	GLSS100
0-160	20	2	GLSS160
0-200	50	5	GLSS200
0-300	50	5	GLSS300
0-400	100	10	GLSS400
0-600	100	10	GLSS600
0-1000	200	20	GLSS1000
0-1500	300	20	GLSS1500
0-2000	500	50	GLSS2000
0-3000	500	50	GLSS3000
0-5000	1000	100	GLSS5000
0-10000	2000	200	GLSS10000

### All Stainless Steel Liquid Filled Gauges

**Application**

- Designed for severe service applications, providing the corrosion resistance and durability of a permanently sealed gauge

**Features**

- ± 2-1-2% accuracy
- 1/4" NPT center back mount stainless connector

**Materials**

- Window: polycarbonate
- Case and crimp ring: 304 stainless
- Glycerin filled

**Specification**

- Ambient temperature range: 20°F to 158°F (-7°C to 70°C)



PSI Range	Figure Interval	Minor Gradient	2-1/2" Face 1/4" Center Back Mount Part #
0-100	20	2	GLSSC100
0-160	20	2	GLSSC160
0-200	50	5	GLSSC200